

```
execve("/usr/local/bin/coreform_cubit", ["coreform_cubit"], 0x7fffde7e1d10 /* 20
vars */) = 0
brk(NULL) = 0x9da000
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
readlink("/proc/self/exe", "/opt/Coreform-Cubit-2021.5/bin/c"... , 4096) = 45
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x7f64b4ce0000
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./tls/haswell/avx512_1/x86_64/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./tls/haswell/avx512_1/x86_64",
0x7fffc17b19d0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./tls/haswell/avx512_1/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./tls/haswell/avx512_1", 0x7fffc17b19d0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./tls/haswell/x86_64/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./tls/haswell/x86_64", 0x7fffc17b19d0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./tls/haswell/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./tls/haswell", 0x7fffc17b19d0) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./tls/avx512_1/x86_64/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./tls/avx512_1/x86_64", 0x7fffc17b19d0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./tls/avx512_1/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./tls/avx512_1", 0x7fffc17b19d0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./tls/x86_64/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./tls/x86_64", 0x7fffc17b19d0) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./tls/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./tls", 0x7fffc17b19d0) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./haswell/avx512_1/x86_64/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./haswell/avx512_1/x86_64", 0x7fffc17b19d0)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./haswell/avx512_1/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./haswell/avx512_1", 0x7fffc17b19d0) = -1
ENOENT (No such file or directory)
```

```
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./haswell/x86_64/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./haswell/x86_64", 0x7fffc17b19d0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./haswell/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./haswell", 0x7fffc17b19d0) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./avx512_1/x86_64/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./avx512_1/x86_64", 0x7fffc17b19d0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./avx512_1/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./avx512_1", 0x7fffc17b19d0) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./x86_64/libclarogui.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./x86_64", 0x7fffc17b19d0) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libclarogui.so",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0\>\0\1\0\0\0\340\305\2\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\4\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
784) = 784
lseek(3, 862432, SEEK_SET) = 862432
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0UtTY\214y9\260\202\230\227\2441E\262A"..., 36) =
36
fstat(3, {st_mode=S_IFREG|0755, st_size=1090944, ...}) = 0
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\4\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
784) = 784
mmap(NULL, 1090944, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x7f64b4b1e000
mmap(0x7f64b4b47000, 344064, PROT_READ|PROT_EXEC,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x29000) = 0x7f64b4b47000
mmap(0x7f64b4b9b000, 262144, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3,
0x7d000) = 0x7f64b4b9b000
mmap(0x7f64b4bdb000, 28672, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xbc000) = 0x7f64b4bdb000
mmap(0x7f64b4be2000, 61440, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xc4000) = 0x7f64b4be2000
mmap(0x7f64b4bf1000, 57344, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xd3000) = 0x7f64b4bf1000
mmap(0x7f64b4bff000, 57344, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xe1000) = 0x7f64b4bff000
mmap(0x7f64b4c0d000, 57344, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xef000) = 0x7f64b4c0d000
mmap(0x7f64b4c1b000, 57344, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xfd000) = 0x7f64b4c1b000
```

```
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/tls/haswell/avx512_1/x86_64/libpthread.so
.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/tls/haswell/avx512_1/x86_64",
0x7fffc17b19a0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/tls/haswell/avx512_1/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/tls/haswell/avx512_1",
0x7fffc17b19a0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/tls/haswell/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/tls/haswell/x86_64", 0x7fffc17b19a0)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/tls/haswell/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/tls/haswell", 0x7fffc17b19a0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/tls/avx512_1/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/tls/avx512_1/x86_64",
0x7fffc17b19a0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/tls/avx512_1/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/tls/avx512_1", 0x7fffc17b19a0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/tls/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/tls/x86_64", 0x7fffc17b19a0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/tls/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/tls", 0x7fffc17b19a0) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/haswell/avx512_1/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/haswell/avx512_1/x86_64",
0x7fffc17b19a0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/haswell/avx512_1/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/haswell/avx512_1", 0x7fffc17b19a0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/haswell/x86_64/libpthread.so.0",
```

```
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/haswell/x86_64", 0x7fffc17b19a0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/haswell/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/haswell", 0x7fffc17b19a0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/avx512_1/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/avx512_1/x86_64", 0x7fffc17b19a0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/avx512_1/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/avx512_1", 0x7fffc17b19a0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib/x86_64", 0x7fffc17b19a0) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./lib", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/tls/haswell/avx512_1/x86_64/libpthread.so
.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/tls/haswell/avx512_1/x86_64",
0x7fffc17b19a0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/tls/haswell/avx512_1/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/tls/haswell/avx512_1",
0x7fffc17b19a0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/tls/haswell/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/tls/haswell/x86_64", 0x7fffc17b19a0)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/tls/haswell/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/tls/haswell", 0x7fffc17b19a0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/tls/avx512_1/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/tls/avx512_1/x86_64",
0x7fffc17b19a0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/tls/avx512_1/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
```

```
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/tls/avx512_1", 0x7fffc17b19a0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/tls/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/tls/x86_64", 0x7fffc17b19a0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/tls/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/tls", 0x7fffc17b19a0) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/haswell/avx512_1/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/haswell/avx512_1/x86_64",
0x7fffc17b19a0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/haswell/avx512_1/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/haswell/avx512_1", 0x7fffc17b19a0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/haswell/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/haswell/x86_64", 0x7fffc17b19a0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/haswell/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/haswell", 0x7fffc17b19a0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/avx512_1/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/avx512_1/x86_64", 0x7fffc17b19a0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/avx512_1/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/avx512_1", 0x7fffc17b19a0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin/x86_64", 0x7fffc17b19a0) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./bin", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libpthread.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libpthread.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libpthread.so.0", O_RDONLY|O_CLOEXEC) = -1
```



```
mmap(0x7f64b47d1000, 20480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x12e000) = 0x7f64b47d1000
mmap(0x7f64b47d6000, 20480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x133000) = 0x7f64b47d6000
mmap(0x7f64b47db000, 20480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x138000) = 0x7f64b47db000
close(3)
= 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libQt5Widgets.so.5",
O_RDONLY|O_CLOEXEC) = 3
read(3,
"\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\260\317\25\0\0\0\0"..., 832) =
832
lseek(3, 64, SEEK_SET)
= 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
1400) = 1400
lseek(3, 8631568, SEEK_SET)
= 8631568
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0%\250\364\36\37mN\330\270\22\0044&\237\27\251"...,
36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=16363056, ...}) = 0
lseek(3, 64, SEEK_SET)
= 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
1400) = 1400
mmap(NULL, 17051184, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64b3650000
mprotect(0x7f64b3c80000, 10108928, PROT_NONE) = 0
mmap(0x7f64b3e7f000, 208896, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x62f000) = 0x7f64b3e7f000
mmap(0x7f64b3eb2000, 532480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x7ba000) = 0x7f64b3eb2000
mmap(0x7f64b3f34000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x83c000) = 0x7f64b3f34000
mmap(0x7f64b3fa3000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x8ab000) = 0x7f64b3fa3000
mmap(0x7f64b4012000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x91a000) = 0x7f64b4012000
mmap(0x7f64b4081000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x989000) = 0x7f64b4081000
mmap(0x7f64b40f0000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x9f8000) = 0x7f64b40f0000
mmap(0x7f64b415f000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa67000) = 0x7f64b415f000
mmap(0x7f64b41ce000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xad6000) = 0x7f64b41ce000
mmap(0x7f64b423d000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xb45000) = 0x7f64b423d000
mmap(0x7f64b42ac000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xbb4000) = 0x7f64b42ac000
mmap(0x7f64b431b000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xc23000) = 0x7f64b431b000
mmap(0x7f64b438a000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xc92000) = 0x7f64b438a000
mmap(0x7f64b43f9000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xd01000) = 0x7f64b43f9000
```



```
mmap(0x7f64b4468000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xd70000) = 0x7f64b4468000
mmap(0x7f64b44d7000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xddf000) = 0x7f64b44d7000
mmap(0x7f64b4546000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xe4e000) = 0x7f64b4546000
mmap(0x7f64b45b5000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xebd000) = 0x7f64b45b5000
mmap(0x7f64b4624000, 454656, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xf2c000) = 0x7f64b4624000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libQt5Gui.so.5",
O_RDONLY|O_CLOEXEC) = 3
read(3,
"\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\240\310\16\0\0\0\0"... , 832) =
832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"... ,
5880) = 5880
lseek(3, 9263112, SEEK_SET) = 9263112
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\214~\356\362/\265,\261\244\35|\260|r5i"... , 36)
= 36
fstat(3, {st_mode=S_IFREG|0755, st_size=49452632, ...}) = 0
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x7f64b4cd0000
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"... ,
5880) = 5880
mmap(NULL, 50312792, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64b0650000
mprotect(0x7f64b0d60000, 42491904, PROT_NONE) = 0
mmap(0x7f64b0f5f000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x70f000) = 0x7f64b0f5f000
mmap(0x7f64b0f76000, 44360, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64b0f76000
mmap(0x7f64b0f81000, 487424, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x85f000) = 0x7f64b0f81000
mmap(0x7f64b0ff8000, 409600, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x8d6000) = 0x7f64b0ff8000
mmap(0x7f64b105c000, 409600, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x93a000) = 0x7f64b105c000
mmap(0x7f64b10c0000, 409600, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x99e000) = 0x7f64b10c0000
mmap(0x7f64b1124000, 409600, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa02000) = 0x7f64b1124000
mmap(0x7f64b1188000, 409600, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa66000) = 0x7f64b1188000
mmap(0x7f64b11ec000, 409600, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xaca000) = 0x7f64b11ec000
mmap(0x7f64b1250000, 409600, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xb2e000) = 0x7f64b1250000
mmap(0x7f64b12b4000, 409600, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xb92000) = 0x7f64b12b4000
```

mmap(0x7f64b1318000, 409600, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xbf6000) = 0x7f64b1318000
mmap(0x7f64b137c000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xc5a000) = 0x7f64b137c000
mmap(0x7f64b13e1000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xcbf000) = 0x7f64b13e1000
mmap(0x7f64b1446000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xd24000) = 0x7f64b1446000
mmap(0x7f64b14ab000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xd89000) = 0x7f64b14ab000
mmap(0x7f64b1510000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xdee000) = 0x7f64b1510000
mmap(0x7f64b1575000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xe53000) = 0x7f64b1575000
mmap(0x7f64b15da000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xeb8000) = 0x7f64b15da000
mmap(0x7f64b163f000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xf1d000) = 0x7f64b163f000
mmap(0x7f64b16a4000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xf82000) = 0x7f64b16a4000
mmap(0x7f64b1709000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xfe7000) = 0x7f64b1709000
mmap(0x7f64b176e000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x104c000) = 0x7f64b176e000
mmap(0x7f64b17d3000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x10b1000) = 0x7f64b17d3000
mmap(0x7f64b1838000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1116000) = 0x7f64b1838000
mmap(0x7f64b189d000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x117b000) = 0x7f64b189d000
mmap(0x7f64b1902000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x11e0000) = 0x7f64b1902000
mmap(0x7f64b1967000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1245000) = 0x7f64b1967000
mmap(0x7f64b19cc000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x12aa000) = 0x7f64b19cc000
mmap(0x7f64b1a31000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x130f000) = 0x7f64b1a31000
mmap(0x7f64b1a96000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1374000) = 0x7f64b1a96000
mmap(0x7f64b1afb000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x13d9000) = 0x7f64b1afb000
mmap(0x7f64b1b60000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x143e000) = 0x7f64b1b60000
mmap(0x7f64b1bc5000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x14a3000) = 0x7f64b1bc5000
mmap(0x7f64b1c2a000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1508000) = 0x7f64b1c2a000
mmap(0x7f64b1c8f000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x156d000) = 0x7f64b1c8f000
mmap(0x7f64b1cf4000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x15d2000) = 0x7f64b1cf4000
mmap(0x7f64b1d59000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1637000) = 0x7f64b1d59000

mmap(0x7f64b1dbe000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x169c000) = 0x7f64b1dbe000
mmap(0x7f64b1e23000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1701000) = 0x7f64b1e23000
mmap(0x7f64b1e88000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1766000) = 0x7f64b1e88000
mmap(0x7f64b1eed000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x17cb000) = 0x7f64b1eed000
mmap(0x7f64b1f52000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1830000) = 0x7f64b1f52000
mmap(0x7f64b1fb7000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1895000) = 0x7f64b1fb7000
mmap(0x7f64b201c000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x18fa000) = 0x7f64b201c000
mmap(0x7f64b2081000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x195f000) = 0x7f64b2081000
mmap(0x7f64b20e6000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x19c4000) = 0x7f64b20e6000
mmap(0x7f64b214b000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1a29000) = 0x7f64b214b000
mmap(0x7f64b21b0000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1a8e000) = 0x7f64b21b0000
mmap(0x7f64b2215000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1af3000) = 0x7f64b2215000
mmap(0x7f64b227a000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1b58000) = 0x7f64b227a000
mmap(0x7f64b22df000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1bbd000) = 0x7f64b22df000
mmap(0x7f64b2344000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1c22000) = 0x7f64b2344000
mmap(0x7f64b23a9000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1c87000) = 0x7f64b23a9000
mmap(0x7f64b240e000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1cec000) = 0x7f64b240e000
mmap(0x7f64b2473000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1d51000) = 0x7f64b2473000
mmap(0x7f64b24d8000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1db6000) = 0x7f64b24d8000
mmap(0x7f64b253d000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1e1b000) = 0x7f64b253d000
mmap(0x7f64b25a2000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1e80000) = 0x7f64b25a2000
mmap(0x7f64b2607000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1ee5000) = 0x7f64b2607000
mmap(0x7f64b266c000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1f4a000) = 0x7f64b266c000
mmap(0x7f64b26d1000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1faf000) = 0x7f64b26d1000
mmap(0x7f64b2736000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2014000) = 0x7f64b2736000
mmap(0x7f64b279b000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2079000) = 0x7f64b279b000
mmap(0x7f64b2800000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x20de000) = 0x7f64b2800000

mmap(0x7f64b2865000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2143000) = 0x7f64b2865000
mmap(0x7f64b28ca000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x21a8000) = 0x7f64b28ca000
mmap(0x7f64b292f000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x220d000) = 0x7f64b292f000
mmap(0x7f64b2994000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2272000) = 0x7f64b2994000
mmap(0x7f64b29f9000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x22d7000) = 0x7f64b29f9000
mmap(0x7f64b2a5e000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x233c000) = 0x7f64b2a5e000
mmap(0x7f64b2ac3000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x23a1000) = 0x7f64b2ac3000
mmap(0x7f64b2b28000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2406000) = 0x7f64b2b28000
mmap(0x7f64b2b8d000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x246b000) = 0x7f64b2b8d000
mmap(0x7f64b2bf2000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x24d0000) = 0x7f64b2bf2000
mmap(0x7f64b2c57000, 413696, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2535000) = 0x7f64b2c57000
mmap(0x7f64b2cbc000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x259a000) = 0x7f64b2cbc000
mmap(0x7f64b2d22000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2600000) = 0x7f64b2d22000
mmap(0x7f64b2d88000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2666000) = 0x7f64b2d88000
mmap(0x7f64b2dee000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x26cc000) = 0x7f64b2dee000
mmap(0x7f64b2e54000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2732000) = 0x7f64b2e54000
mmap(0x7f64b2eba000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2798000) = 0x7f64b2eba000
mmap(0x7f64b2f20000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x27fe000) = 0x7f64b2f20000
mmap(0x7f64b2f86000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2864000) = 0x7f64b2f86000
mmap(0x7f64b2fec000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x28ca000) = 0x7f64b2fec000
mmap(0x7f64b3052000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2930000) = 0x7f64b3052000
mmap(0x7f64b30b8000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2996000) = 0x7f64b30b8000
mmap(0x7f64b311e000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x29fc000) = 0x7f64b311e000
mmap(0x7f64b3184000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2a62000) = 0x7f64b3184000
mmap(0x7f64b31ea000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2ac8000) = 0x7f64b31ea000
mmap(0x7f64b3250000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2b2e000) = 0x7f64b3250000
mmap(0x7f64b32b6000, 417792, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2b94000) = 0x7f64b32b6000

```
mmap(0x7f64b331c000, 417792, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2bfa000) = 0x7f64b331c000
mmap(0x7f64b3382000, 417792, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2c60000) = 0x7f64b3382000
mmap(0x7f64b33e8000, 417792, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2cc6000) = 0x7f64b33e8000
mmap(0x7f64b344e000, 417792, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2d2c000) = 0x7f64b344e000
mmap(0x7f64b34b4000, 417792, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2d92000) = 0x7f64b34b4000
mmap(0x7f64b351a000, 417792, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2df8000) = 0x7f64b351a000
mmap(0x7f64b3580000, 417792, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2e5e000) = 0x7f64b3580000
mmap(0x7f64b35e6000, 417792, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2ec4000) = 0x7f64b35e6000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libQt5Core.so.5",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\320z\n\0\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\6\0\0\0\5\0\0\0@\0\0\0\0\0\0@\0\0\0\0\0\0@\0\0\0\0\0\0"...,
7392) = 7392
lseek(3, 6176464, SEEK_SET) = 6176464
read(3, "\4\0\0\0\20\0\0\0\1\0\0\0GNU\0\0\0\0\2\0\0\0\6\0\0\0\34\0\0\0", 32) =
32
fstat(3, {st_mode=S_IFREG|0755, st_size=38237360, ...}) = 0
lseek(3, 64, SEEK_SET) = 64
read(3, "\6\0\0\0\5\0\0\0@\0\0\0\0\0\0@\0\0\0\0\0\0@\0\0\0\0\0\0"...,
7392) = 7392
mmap(NULL, 39511216, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64ae0a0000
mprotect(0x7f64ae684000, 33075200, PROT_NONE) = 0
mmap(0x7f64ae884000, 61440, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5e4000) = 0x7f64ae884000
mmap(0x7f64ae893000, 12072, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64ae893000
mmap(0x7f64ae896000, 303104, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x6bf000) = 0x7f64ae896000
mmap(0x7f64ae8e0000, 253952, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x709000) = 0x7f64ae8e0000
mmap(0x7f64ae91e000, 253952, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x747000) = 0x7f64ae91e000
mmap(0x7f64ae95c000, 253952, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x785000) = 0x7f64ae95c000
mmap(0x7f64ae99a000, 253952, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x7c3000) = 0x7f64ae99a000
mmap(0x7f64ae9d8000, 253952, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x801000) = 0x7f64ae9d8000
mmap(0x7f64aea16000, 253952, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x83f000) = 0x7f64aea16000
mmap(0x7f64aea54000, 253952, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x87d000) = 0x7f64aea54000
```

mmap(0x7f64aea92000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x8bb000) = 0x7f64aea92000
mmap(0x7f64ead0000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x8f9000) = 0x7f64ead0000
mmap(0x7f64aeb0e000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x937000) = 0x7f64aeb0e000
mmap(0x7f64aeb4c000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x975000) = 0x7f64aeb4c000
mmap(0x7f64aeb8a000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x9b3000) = 0x7f64aeb8a000
mmap(0x7f64aebc8000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x9f1000) = 0x7f64aebc8000
mmap(0x7f64aec06000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa2f000) = 0x7f64aec06000
mmap(0x7f64aec44000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa6d000) = 0x7f64aec44000
mmap(0x7f64aec82000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xaab000) = 0x7f64aec82000
mmap(0x7f64aecc0000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xae9000) = 0x7f64aecc0000
mmap(0x7f64aecfe000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xb27000) = 0x7f64aecfe000
mmap(0x7f64aed3c000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xb65000) = 0x7f64aed3c000
mmap(0x7f64aed7a000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xba3000) = 0x7f64aed7a000
mmap(0x7f64aedb8000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xbe1000) = 0x7f64aedb8000
mmap(0x7f64aedf6000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xc1f000) = 0x7f64aedf6000
mmap(0x7f64aee34000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xc5d000) = 0x7f64aee34000
mmap(0x7f64aee72000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xc9b000) = 0x7f64aee72000
mmap(0x7f64aeeb0000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xcd9000) = 0x7f64aeeb0000
mmap(0x7f64aeeee000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xd17000) = 0x7f64aeeee000
mmap(0x7f64aef2c000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xd55000) = 0x7f64aef2c000
mmap(0x7f64aef6a000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xd93000) = 0x7f64aef6a000
mmap(0x7f64aefa8000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xdd1000) = 0x7f64aefa8000
mmap(0x7f64aeefe000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xe0f000) = 0x7f64aeefe000
mmap(0x7f64af024000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xe4d000) = 0x7f64af024000
mmap(0x7f64af062000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xe8b000) = 0x7f64af062000
mmap(0x7f64af0a0000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xec9000) = 0x7f64af0a0000
mmap(0x7f64af0de000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xf07000) = 0x7f64af0de000

mmap(0x7f64af11c000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xf45000) = 0x7f64af11c000
mmap(0x7f64af15a000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xf83000) = 0x7f64af15a000
mmap(0x7f64af198000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xfc1000) = 0x7f64af198000
mmap(0x7f64af1d6000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xffff000) = 0x7f64af1d6000
mmap(0x7f64af214000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x103d000) = 0x7f64af214000
mmap(0x7f64af252000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x107b000) = 0x7f64af252000
mmap(0x7f64af290000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x10b9000) = 0x7f64af290000
mmap(0x7f64af2ce000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x10f7000) = 0x7f64af2ce000
mmap(0x7f64af30c000, 253952, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1135000) = 0x7f64af30c000
mmap(0x7f64af34a000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1173000) = 0x7f64af34a000
mmap(0x7f64af389000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x11b2000) = 0x7f64af389000
mmap(0x7f64af3c8000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x11f1000) = 0x7f64af3c8000
mmap(0x7f64af407000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1230000) = 0x7f64af407000
mmap(0x7f64af446000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x126f000) = 0x7f64af446000
mmap(0x7f64af485000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x12ae000) = 0x7f64af485000
mmap(0x7f64af4c4000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x12ed000) = 0x7f64af4c4000
mmap(0x7f64af503000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x132c000) = 0x7f64af503000
mmap(0x7f64af542000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x136b000) = 0x7f64af542000
mmap(0x7f64af581000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x13aa000) = 0x7f64af581000
mmap(0x7f64af5c0000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x13e9000) = 0x7f64af5c0000
mmap(0x7f64af5ff000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1428000) = 0x7f64af5ff000
mmap(0x7f64af63e000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1467000) = 0x7f64af63e000
mmap(0x7f64af67d000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x14a6000) = 0x7f64af67d000
mmap(0x7f64af6bc000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x14e5000) = 0x7f64af6bc000
mmap(0x7f64af6fb000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1524000) = 0x7f64af6fb000
mmap(0x7f64af73a000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1563000) = 0x7f64af73a000
mmap(0x7f64af779000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x15a2000) = 0x7f64af779000

mmap(0x7f64af7b8000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x15e1000) = 0x7f64af7b8000
mmap(0x7f64af7f7000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1620000) = 0x7f64af7f7000
mmap(0x7f64af836000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x165f000) = 0x7f64af836000
mmap(0x7f64af875000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x169e000) = 0x7f64af875000
mmap(0x7f64af8b4000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x16dd000) = 0x7f64af8b4000
mmap(0x7f64af8f3000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x171c000) = 0x7f64af8f3000
mmap(0x7f64af932000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x175b000) = 0x7f64af932000
mmap(0x7f64af971000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x179a000) = 0x7f64af971000
mmap(0x7f64af9b0000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x17d9000) = 0x7f64af9b0000
mmap(0x7f64af9ef000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1818000) = 0x7f64af9ef000
mmap(0x7f64afa2e000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1857000) = 0x7f64afa2e000
mmap(0x7f64afa6d000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1896000) = 0x7f64afa6d000
mmap(0x7f64afaac000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x18d5000) = 0x7f64afaac000
mmap(0x7f64afaeb000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1914000) = 0x7f64afaeb000
mmap(0x7f64afb2a000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1953000) = 0x7f64afb2a000
mmap(0x7f64afb69000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1992000) = 0x7f64afb69000
mmap(0x7f64afba8000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x19d1000) = 0x7f64afba8000
mmap(0x7f64afbe7000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1a10000) = 0x7f64afbe7000
mmap(0x7f64afc26000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1a4f000) = 0x7f64afc26000
mmap(0x7f64afc65000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1a8e000) = 0x7f64afc65000
mmap(0x7f64afca4000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1acd000) = 0x7f64afca4000
mmap(0x7f64afce3000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1b0c000) = 0x7f64afce3000
mmap(0x7f64afd22000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1b4b000) = 0x7f64afd22000
mmap(0x7f64afd61000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1b8a000) = 0x7f64afd61000
mmap(0x7f64afda0000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1bc9000) = 0x7f64afda0000
mmap(0x7f64afddf000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1c08000) = 0x7f64afddf000
mmap(0x7f64afe1e000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1c47000) = 0x7f64afe1e000

mmap(0x7f64afe5d000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1c86000) = 0x7f64afe5d000
mmap(0x7f64afe9c000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1cc5000) = 0x7f64afe9c000
mmap(0x7f64afedb000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1d04000) = 0x7f64afedb000
mmap(0x7f64aff1a000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1d43000) = 0x7f64aff1a000
mmap(0x7f64aff59000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1d82000) = 0x7f64aff59000
mmap(0x7f64aff98000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1dc1000) = 0x7f64aff98000
mmap(0x7f64affd7000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1e00000) = 0x7f64affd7000
mmap(0x7f64b0016000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1e3f000) = 0x7f64b0016000
mmap(0x7f64b0055000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1e7e000) = 0x7f64b0055000
mmap(0x7f64b0094000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1ebd000) = 0x7f64b0094000
mmap(0x7f64b00d3000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1efc000) = 0x7f64b00d3000
mmap(0x7f64b0112000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1f3b000) = 0x7f64b0112000
mmap(0x7f64b0151000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1f7a000) = 0x7f64b0151000
mmap(0x7f64b0190000, 258048, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1fb9000) = 0x7f64b0190000
mmap(0x7f64b01cf000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1ff8000) = 0x7f64b01cf000
mmap(0x7f64b020f000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2038000) = 0x7f64b020f000
mmap(0x7f64b024f000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2078000) = 0x7f64b024f000
mmap(0x7f64b028f000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x20b8000) = 0x7f64b028f000
mmap(0x7f64b02cf000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x20f8000) = 0x7f64b02cf000
mmap(0x7f64b030f000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2138000) = 0x7f64b030f000
mmap(0x7f64b034f000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2178000) = 0x7f64b034f000
mmap(0x7f64b038f000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x21b8000) = 0x7f64b038f000
mmap(0x7f64b03cf000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x21f8000) = 0x7f64b03cf000
mmap(0x7f64b040f000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2238000) = 0x7f64b040f000
mmap(0x7f64b044f000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2278000) = 0x7f64b044f000
mmap(0x7f64b048f000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x22b8000) = 0x7f64b048f000
mmap(0x7f64b04cf000, 262144, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x22f8000) = 0x7f64b04cf000

```
mmap(0x7f64b050f000, 262144, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2338000) = 0x7f64b050f000
mmap(0x7f64b054f000, 262144, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2378000) = 0x7f64b054f000
mmap(0x7f64b058f000, 262144, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x23b8000) = 0x7f64b058f000
mmap(0x7f64b05cf000, 262144, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x23f8000) = 0x7f64b05cf000
mmap(0x7f64b060f000, 262144, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2438000) = 0x7f64b060f000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libvtkCommonCore-8.2.so.1",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\220\350\f\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\4\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
896) = 896
lseek(3, 5450560, SEEK_SET) = 5450560
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0c\260\312\''\327\227\351\273\314&L\342\303\247/"
.., 36) = 36
fstat(3, {st_mode=S_IFREG|0644, st_size=6875960, ...}) = 0
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\4\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
896) = 896
mmap(NULL, 6040376, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x7f64adadd000
mprotect(0x7f64adba5000, 4984832, PROT_NONE) = 0
mmap(0x7f64adba5000, 2781184, PROT_READ|PROT_EXEC,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xc8000) = 0x7f64adba5000
mmap(0x7f64ade4c000, 577536, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3,
0x36f000) = 0x7f64ade4c000
mmap(0x7f64adeda000, 151552, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3fc000) = 0x7f64adeda000
mmap(0x7f64adef000, 2776, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64adef000
mmap(0x7f64adf00000, 278528, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4ef000) = 0x7f64adf00000
mmap(0x7f64adf44000, 237568, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x533000) = 0x7f64adf44000
mmap(0x7f64adf7e000, 237568, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x56d000) = 0x7f64adf7e000
mmap(0x7f64adfb8000, 237568, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5a7000) = 0x7f64adfb8000
mmap(0x7f64adff2000, 237568, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5e1000) = 0x7f64adff2000
mmap(0x7f64ae02c000, 237568, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x61b000) = 0x7f64ae02c000
mmap(0x7f64ae066000, 237568, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x655000) = 0x7f64ae066000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libX11.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libX11.so.6",
```

```
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libX11.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libX11.so.6", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/x86_64/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "x86_64/libX11.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "libX11.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libX11.so.6", O_RDONLY|O_CLOEXEC) =
3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0\>\0\1\0\0\0\300\207\1\0\0\0\0"...,
832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=1277384, ...}) = 0
mmap(NULL, 3374392, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64ad7a0000
mprotect(0x7f64ad8d3000, 2097152, PROT_NONE) = 0
mmap(0x7f64adad3000, 20480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x133000) = 0x7f64adad3000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libdl.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libdl.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libdl.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libdl.so.2", O_RDONLY|O_CLOEXEC) =
```

```
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/x86_64/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file
or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "x86_64/libdl.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "libdl.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/lib/x86_64-linux-gnu/libdl.so.2", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0P\16\0\0\0\0\0"...
, 832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=14560, ...}) = 0
mmap(NULL, 2109712, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64ad590000
mprotect(0x7f64ad593000, 2093056, PROT_NONE) = 0
mmap(0x7f64ad792000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2000) = 0x7f64ad792000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libstdc++.so.6",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\3\0>\0\1\0\0\0@\17\n\0\0\0\0"...
, 832) = 832
fstat(3, {st_mode=S_IFREG|0755, st_size=22849096, ...}) = 0
mmap(NULL, 2291272, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x7f64ad360000
mprotect(0x7f64ad3fd000, 1323008, PROT_NONE) = 0
mmap(0x7f64ad3fd000, 950272, PROT_READ|PROT_EXEC,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x9d000) = 0x7f64ad3fd000
mmap(0x7f64ad4e5000, 303104, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3,
0x185000) = 0x7f64ad4e5000
mmap(0x7f64ad52f000, 57344, PROT_READ|PROT_WRITE,
```

```
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1ce000) = 0x7f64ad52f000
mmap(0x7f64ad53d000, 9664, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64ad53d000
mmap(0x7f64ad540000, 327680, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x157b000) = 0x7f64ad540000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libm.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libm.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libm.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libm.so.6", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libm.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libm.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/haswell/libm.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libm.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libm.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/x86_64/libm.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/libm.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file
or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libm.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libm.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libm.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/libm.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libm.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/libm.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "x86_64/libm.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "libm.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/lib/x86_64-linux-gnu/libm.so.6", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\0\0\0\3\0\>\0\1\0\0\0\200\272\0\0\0\0\0"...
, 832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=1700792, ...}) = 0
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x7f64b4c30000
mmap(NULL, 3789144, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64acfc0000
mprotect(0x7f64ad15d000, 2093056, PROT_NONE) = 0
```

```
mmap(0x7f64ad35c000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x19c000) = 0x7f64ad35c000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libgcc_s.so.1",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0\>\0\1\0\0\0\3402\0\0\0\0\0"... ,
832) = 832
fstat(3, {st_mode=S_IFREG|0755, st_size=884608, ...}) = 0
mmap(NULL, 110464, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x7f64b4b03000
mprotect(0x7f64b4b06000, 94208, PROT_NONE) = 0
mmap(0x7f64b4b06000, 69632, PROT_READ|PROT_EXEC,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3000) = 0x7f64b4b06000
mmap(0x7f64b4b17000, 12288, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3,
0x14000) = 0x7f64b4b17000
mmap(0x7f64b4b1b000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x17000) = 0x7f64b4b1b000
mmap(0x7f64b4b1d000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xd7000) = 0x7f64b4b1d000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libc.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libc.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libc.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libc.so.6", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libc.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libc.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/haswell/libc.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libc.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libc.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/x86_64/libc.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/libc.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file
or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libc.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libc.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libc.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/libc.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libc.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/libc.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "x86_64/libc.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
```

```
file or directory)
openat(AT_FDCWD, "libc.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/lib/x86_64-linux-gnu/libc.so.6", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0\>\0\1\0\0\0\20\35\2\0\0\0\0"...,
832) = 832
fstat(3, {st_mode=S_IFREG|0755, st_size=2030928, ...}) = 0
mmap(NULL, 4131552, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64acbc0000
mprotect(0x7f64acda7000, 2097152, PROT_NONE) = 0
mmap(0x7f64acfa7000, 24576, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1e7000) = 0x7f64acfa7000
mmap(0x7f64acfad000, 15072, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64acfad000
close(3) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././tls/haswell/avx512_1/x86_64/libnavigation.so
", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././tls/haswell/avx512_1/x86_64",
0x7fffc17b1570) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././tls/haswell/avx512_1/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././tls/haswell/avx512_1", 0x7fffc17b1570)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././tls/haswell/x86_64/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././tls/haswell/x86_64", 0x7fffc17b1570) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././tls/haswell/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././tls/haswell", 0x7fffc17b1570) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././tls/avx512_1/x86_64/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././tls/avx512_1/x86_64", 0x7fffc17b1570) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././tls/avx512_1/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././tls/avx512_1", 0x7fffc17b1570) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././tls/x86_64/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././tls/x86_64", 0x7fffc17b1570) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././tls/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././tls", 0x7fffc17b1570) = -1 ENOENT (No
```

```
such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././haswell/avx512_1/x86_64/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././haswell/avx512_1/x86_64",
0x7fffc17b1570) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././haswell/avx512_1/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././haswell/avx512_1", 0x7fffc17b1570) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././haswell/x86_64/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././haswell/x86_64", 0x7fffc17b1570) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././haswell/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././haswell", 0x7fffc17b1570) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././avx512_1/x86_64/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././avx512_1/x86_64", 0x7fffc17b1570) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././avx512_1/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././avx512_1", 0x7fffc17b1570) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././x86_64/libnavigation.so",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././x86_64", 0x7fffc17b1570) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././libnavigation.so",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\\177ELF\\2\\1\\1\\3\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\3\\0>\\0\\1\\0\\0\\0\\360J\\1\\0\\0\\0\\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\\1\\0\\0\\0\\4\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0"...,
784) = 784
lseek(3, 298744, SEEK_SET) = 298744
read(3,
"\4\\0\\0\\0\\24\\0\\0\\0\\3\\0\\0\\0GNU\\0\\212\\3\\247\\27\\250h05\\356-\\224\\271\\357y\\333y"...,
36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=427456, ...}) = 0
lseek(3, 64, SEEK_SET) = 64
read(3, "\\1\\0\\0\\0\\4\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0\\0"...,
784) = 784
mmap(NULL, 427456, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x7f64b4a9a000
mprotect(0x7f64b4aad000, 319488, PROT_NONE) = 0
mmap(0x7f64b4aad000, 131072, PROT_READ|PROT_EXEC,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x13000) = 0x7f64b4aad000
mmap(0x7f64b4acd000, 40960, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3,
0x33000) = 0x7f64b4acd000
```



```
mmap(0x7f64b4ad8000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3d000) = 0x7f64b4ad8000
mmap(0x7f64b4adb000, 32768, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x41000) = 0x7f64b4adb000
mmap(0x7f64b4ae3000, 32768, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x49000) = 0x7f64b4ae3000
mmap(0x7f64b4aeb000, 32768, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x51000) = 0x7f64b4aeb000
mmap(0x7f64b4af3000, 32768, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x59000) = 0x7f64b4af3000
mmap(0x7f64b4afb000, 32768, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x61000) = 0x7f64b4afb000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././libcubit_python.so",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0@\250\0\0\0\0\0"...
, 832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\4\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...
, 1176) = 1176
lseek(3, 274592, SEEK_SET) = 274592
read(3, "\4\0\0\0\24\0\0\0\3\0\0\0GNU\0[\355x\312U2\3<XLUS,\320\2369"...
, 36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=373920, ...}) = 0
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\4\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...
, 1176) = 1176
mmap(NULL, 373920, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x7f64b4a3e000
mmap(0x7f64b4a48000, 159744, PROT_READ|PROT_EXEC,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa000) = 0x7f64b4a48000
mmap(0x7f64b4a6f000, 49152, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3,
0x31000) = 0x7f64b4a6f000
mmap(0x7f64b4a7b000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3c000) = 0x7f64b4a7b000
mmap(0x7f64b4a7f000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x41000) = 0x7f64b4a7f000
mmap(0x7f64b4a82000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x44000) = 0x7f64b4a82000
mmap(0x7f64b4a84000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x46000) = 0x7f64b4a84000
mmap(0x7f64b4a86000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x48000) = 0x7f64b4a86000
mmap(0x7f64b4a88000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4a000) = 0x7f64b4a88000
mmap(0x7f64b4a8a000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4c000) = 0x7f64b4a8a000
mmap(0x7f64b4a8c000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4e000) = 0x7f64b4a8c000
mmap(0x7f64b4a8e000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x50000) = 0x7f64b4a8e000
mmap(0x7f64b4a90000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x52000) = 0x7f64b4a90000
mmap(0x7f64b4a93000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x55000) = 0x7f64b4a93000
```

```
mmap(0x7f64b4a96000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x58000) = 0x7f64b4a96000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././libcubit_util.so",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\3\0\>\0\1\0\0\0`s\3\0\0\0\0"..., 832)
= 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\4\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
1344) = 1344
lseek(3, 1159968, SEEK_SET) = 1159968
read(3, "\4\0\0\0\24\0\0\0\3\0\0\0GNU\0T\261:qr\342
\276/\206\3563\213\226y\256"..., 36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=2368048, ...}) = 0
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x7f64b4a30000
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\4\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
1344) = 1344
mmap(NULL, 2376240, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x7f64ac970000
mprotect(0x7f64ac9a4000, 2072576, PROT_NONE) = 0
mmap(0x7f64ac9a4000, 643072, PROT_READ|PROT_EXEC,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x34000) = 0x7f64ac9a4000
mmap(0x7f64aca41000, 172032, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3,
0xd1000) = 0x7f64aca41000
mmap(0x7f64aca6c000, 28672, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xfb000) = 0x7f64aca6c000
mmap(0x7f64aca73000, 3704, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64aca73000
mmap(0x7f64aca74000, 106496, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x102000) = 0x7f64aca74000
mmap(0x7f64aca8e000, 90112, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x11c000) = 0x7f64aca8e000
mmap(0x7f64acaa4000, 90112, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x132000) = 0x7f64acaa4000
mmap(0x7f64acaba000, 90112, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x148000) = 0x7f64acaba000
mmap(0x7f64acad000, 90112, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x15e000) = 0x7f64acad000
mmap(0x7f64acae6000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x174000) = 0x7f64acae6000
mmap(0x7f64acafd000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x18b000) = 0x7f64acafd000
mmap(0x7f64acb14000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1a2000) = 0x7f64acb14000
mmap(0x7f64acb2b000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1b9000) = 0x7f64acb2b000
mmap(0x7f64acb42000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1d0000) = 0x7f64acb42000
mmap(0x7f64acb59000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1e7000) = 0x7f64acb59000
mmap(0x7f64acb70000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1fe000) = 0x7f64acb70000
mmap(0x7f64acb87000, 94208, PROT_READ|PROT_WRITE,
```


MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3d5000) = 0x7f64ac255000
mmap(0x7f64ac26c000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3ec000) = 0x7f64ac26c000
mmap(0x7f64ac283000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x403000) = 0x7f64ac283000
mmap(0x7f64ac29a000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x41a000) = 0x7f64ac29a000
mmap(0x7f64ac2b1000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x431000) = 0x7f64ac2b1000
mmap(0x7f64ac2c8000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x448000) = 0x7f64ac2c8000
mmap(0x7f64ac2df000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x45f000) = 0x7f64ac2df000
mmap(0x7f64ac2f6000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x476000) = 0x7f64ac2f6000
mmap(0x7f64ac30d000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x48d000) = 0x7f64ac30d000
mmap(0x7f64ac324000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4a4000) = 0x7f64ac324000
mmap(0x7f64ac33b000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4bb000) = 0x7f64ac33b000
mmap(0x7f64ac352000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4d2000) = 0x7f64ac352000
mmap(0x7f64ac369000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4e9000) = 0x7f64ac369000
mmap(0x7f64ac380000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x500000) = 0x7f64ac380000
mmap(0x7f64ac397000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x517000) = 0x7f64ac397000
mmap(0x7f64ac3ae000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x52e000) = 0x7f64ac3ae000
mmap(0x7f64ac3c5000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x545000) = 0x7f64ac3c5000
mmap(0x7f64ac3dc000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x55c000) = 0x7f64ac3dc000
mmap(0x7f64ac3f3000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x573000) = 0x7f64ac3f3000
mmap(0x7f64ac40a000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x58a000) = 0x7f64ac40a000
mmap(0x7f64ac421000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5a1000) = 0x7f64ac421000
mmap(0x7f64ac438000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5b8000) = 0x7f64ac438000
mmap(0x7f64ac44f000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5cf000) = 0x7f64ac44f000
mmap(0x7f64ac466000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5e6000) = 0x7f64ac466000
mmap(0x7f64ac47d000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5fd000) = 0x7f64ac47d000
mmap(0x7f64ac494000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x614000) = 0x7f64ac494000
mmap(0x7f64ac4ab000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x62b000) = 0x7f64ac4ab000
mmap(0x7f64ac4c2000, 94208, PROT_READ|PROT_WRITE,

```
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x642000) = 0x7f64ac4c2000
mmap(0x7f64ac4d9000, 94208, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x659000) = 0x7f64ac4d9000
mmap(0x7f64ac4f0000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x670000) = 0x7f64ac4f0000
mmap(0x7f64ac508000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x688000) = 0x7f64ac508000
mmap(0x7f64ac520000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x6a0000) = 0x7f64ac520000
mmap(0x7f64ac538000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x6b8000) = 0x7f64ac538000
mmap(0x7f64ac550000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x6d0000) = 0x7f64ac550000
mmap(0x7f64ac568000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x6e8000) = 0x7f64ac568000
mmap(0x7f64ac580000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x700000) = 0x7f64ac580000
mmap(0x7f64ac598000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x718000) = 0x7f64ac598000
mmap(0x7f64ac5b0000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x730000) = 0x7f64ac5b0000
mmap(0x7f64ac5c8000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x748000) = 0x7f64ac5c8000
mmap(0x7f64ac5e0000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x760000) = 0x7f64ac5e0000
mmap(0x7f64ac5f8000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x778000) = 0x7f64ac5f8000
mmap(0x7f64ac610000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x790000) = 0x7f64ac610000
mmap(0x7f64ac628000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x7a8000) = 0x7f64ac628000
mmap(0x7f64ac640000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x7c0000) = 0x7f64ac640000
mmap(0x7f64ac658000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x7d8000) = 0x7f64ac658000
mmap(0x7f64ac670000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x7f0000) = 0x7f64ac670000
mmap(0x7f64ac688000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x808000) = 0x7f64ac688000
mmap(0x7f64ac6a0000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x820000) = 0x7f64ac6a0000
mmap(0x7f64ac6b8000, 98304, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x838000) = 0x7f64ac6b8000
close(3)
= 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././lib/tls/haswell/avx512_1/x86_64/libGL.so.1"
, O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././lib/tls/haswell/avx512_1/x86_64",
0x7fffc17b1290) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././lib/tls/haswell/avx512_1/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
```

```
stat("/opt/Coreform-Cubit-2021.5/bin/../../lib/tls/haswell/avx512_1",
0x7fffc17b1290) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../lib/tls/haswell/x86_64/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../lib/tls/haswell/x86_64",
0x7fffc17b1290) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../lib/tls/haswell/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../lib/tls/haswell", 0x7fffc17b1290) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../lib/tls/avx512_1/x86_64/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../lib/tls/avx512_1/x86_64",
0x7fffc17b1290) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../lib/tls/avx512_1/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../lib/tls/avx512_1", 0x7fffc17b1290) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../lib/tls/x86_64/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../lib/tls/x86_64", 0x7fffc17b1290) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/../../lib/tls/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../lib/tls", 0x7fffc17b1290) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../lib/haswell/avx512_1/x86_64/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../lib/haswell/avx512_1/x86_64",
0x7fffc17b1290) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../lib/haswell/avx512_1/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../lib/haswell/avx512_1", 0x7fffc17b1290)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../lib/haswell/x86_64/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../lib/haswell/x86_64", 0x7fffc17b1290) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/../../lib/haswell/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../lib/haswell", 0x7fffc17b1290) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../lib/avx512_1/x86_64/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../lib/avx512_1/x86_64", 0x7fffc17b1290)
```

```
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./../lib/avx512_1/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./../lib/avx512_1", 0x7fffc17b1290) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./../lib/x86_64/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./../lib/x86_64", 0x7fffc17b1290) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./../lib/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./../lib", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/haswell/avx512_1/x86_64/libGL.so.1"
, O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/haswell/avx512_1/x86_64",
0x7fffc17b1290) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/haswell/avx512_1/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/haswell/avx512_1",
0x7fffc17b1290) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/haswell/x86_64/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/haswell/x86_64",
0x7fffc17b1290) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/haswell/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/haswell", 0x7fffc17b1290) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/avx512_1/x86_64/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/avx512_1/x86_64",
0x7fffc17b1290) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/avx512_1/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/avx512_1", 0x7fffc17b1290) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/x86_64/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/x86_64", 0x7fffc17b1290) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./../bin/tls/libGL.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./../bin/tls", 0x7fffc17b1290) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./../bin/haswell/avx512_1/x86_64/libGL.so.1",
```



```
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2c000) = 0x7f64aba3b000
mmap(0x7f64aba3c000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2d000) = 0x7f64aba3c000
mmap(0x7f64aba3d000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2e000) = 0x7f64aba3d000
mmap(0x7f64aba3e000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2f000) = 0x7f64aba3e000
mmap(0x7f64aba3f000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x30000) = 0x7f64aba3f000
mmap(0x7f64aba40000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x31000) = 0x7f64aba40000
mmap(0x7f64aba41000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x32000) = 0x7f64aba41000
mmap(0x7f64aba42000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x33000) = 0x7f64aba42000
mmap(0x7f64aba43000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x34000) = 0x7f64aba43000
mmap(0x7f64aba44000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x35000) = 0x7f64aba44000
mmap(0x7f64aba45000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x36000) = 0x7f64aba45000
mmap(0x7f64aba46000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x37000) = 0x7f64aba46000
mmap(0x7f64aba47000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x38000) = 0x7f64aba47000
mmap(0x7f64aba48000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x39000) = 0x7f64aba48000
mmap(0x7f64aba4a000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3b000) = 0x7f64aba4a000
mmap(0x7f64aba4c000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3d000) = 0x7f64aba4c000
mmap(0x7f64aba4e000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3f000) = 0x7f64aba4e000
mmap(0x7f64aba50000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x41000) = 0x7f64aba50000
mmap(0x7f64aba52000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x43000) = 0x7f64aba52000
mmap(0x7f64aba54000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x45000) = 0x7f64aba54000
mmap(0x7f64aba56000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x47000) = 0x7f64aba56000
mmap(0x7f64aba58000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x49000) = 0x7f64aba58000
mmap(0x7f64aba5a000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4b000) = 0x7f64aba5a000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././libcui18n.so.56",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0@\371\v\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
784) = 784
lseek(3, 3804152, SEEK_SET) = 3804152
```

```
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\352j#i\332\350\341\206T;^\17\244\23\313~"...,
36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=6090784, ...}) = 0
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x7f64ab800000
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
784) = 784
mmap(NULL, 7540768, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64ab0c0000
mprotect(0x7f64ab349000, 4501504, PROT_NONE) = 0
mmap(0x7f64ab548000, 65536, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x288000) = 0x7f64ab548000
mmap(0x7f64ab558000, 336, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64ab558000
mmap(0x7f64ab559000, 434176, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x337000) = 0x7f64ab559000
mmap(0x7f64ab5c3000, 380928, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3a1000) = 0x7f64ab5c3000
mmap(0x7f64ab620000, 380928, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3fe000) = 0x7f64ab620000
mmap(0x7f64ab67d000, 380928, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x45b000) = 0x7f64ab67d000
mmap(0x7f64ab6da000, 380928, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4b8000) = 0x7f64ab6da000
mmap(0x7f64ab737000, 380928, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x515000) = 0x7f64ab737000
mmap(0x7f64ab794000, 385024, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x572000) = 0x7f64ab794000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libicuuc.so.56",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0`\202\5\0\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
784) = 784
lseek(3, 2225880, SEEK_SET) = 2225880
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\200\221j5x\304\253\370\331C9\206\267\312\207\356
"... , 36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=3012192, ...}) = 0
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
784) = 784
mmap(NULL, 4839008, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64aac20000
mprotect(0x7f64aac5000, 2985984, PROT_NONE) = 0
mmap(0x7f64aaafc5000, 69632, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1a5000) = 0x7f64aaafc5000
mmap(0x7f64aaafd6000, 7360, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64aaafd6000
mmap(0x7f64aaafd8000, 155648, PROT_READ|PROT_WRITE,
```

```
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1fa000) = 0x7f64aafd8000
mmap(0x7f64aaffe000, 131072, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x220000) = 0x7f64aaffe000
mmap(0x7f64ab01e000, 131072, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x240000) = 0x7f64ab01e000
mmap(0x7f64ab03e000, 131072, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x260000) = 0x7f64ab03e000
mmap(0x7f64ab05e000, 131072, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x280000) = 0x7f64ab05e000
mmap(0x7f64ab07e000, 131072, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2a0000) = 0x7f64ab07e000
mmap(0x7f64ab09e000, 131072, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2c0000) = 0x7f64ab09e000
close(3)
          = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././libcudata.so.56",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\327\2\0\0\0\0\0"...,
832) = 832
lseek(3, 25051720, SEEK_SET)
          = 25051720
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0004\252\303+\264\323\300\364Nr\345|\362S\250q"...
, 36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=50119408, ...}) = 0
mmap(NULL, 52212464, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a7a50000
mprotect(0x7f64a9233000, 27164672, PROT_NONE) = 0
mmap(0x7f64a9432000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x17e2000) = 0x7f64a9432000
mmap(0x7f64a9433000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x17e4000) = 0x7f64a9433000
mmap(0x7f64a9434000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x17e5000) = 0x7f64a9434000
mmap(0x7f64a9435000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x17e6000) = 0x7f64a9435000
mmap(0x7f64a9436000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x17e7000) = 0x7f64a9436000
mmap(0x7f64a9437000, 25047040, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x17e8000) = 0x7f64a9437000
mmap(0x7f64aac1a000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2fcb000) = 0x7f64aac1a000
mmap(0x7f64aac1b000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2fcc000) = 0x7f64aac1b000
close(3)
          = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././libgthread-2.0.so.0",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\240\6\0\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET)
          = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
1064) = 1064
lseek(3, 9512, SEEK_SET)
          = 9512
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\252\322\303\206Y\363\202\237\306\1W\375\\"\31\313
\31"..., 36) = 36
```

```
fstat(3, {st_mode=S_IFREG|0755, st_size=54856, ...}) = 0
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
1064) = 1064
mmap(NULL, 2152008, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a7840000
mprotect(0x7f64a7841000, 2146304, PROT_NONE) = 0
mmap(0x7f64a7a40000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0) = 0x7f64a7a40000
mmap(0x7f64a7a42000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2000) = 0x7f64a7a42000
mmap(0x7f64a7a43000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3000) = 0x7f64a7a43000
mmap(0x7f64a7a44000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4000) = 0x7f64a7a44000
mmap(0x7f64a7a45000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5000) = 0x7f64a7a45000
mmap(0x7f64a7a46000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x6000) = 0x7f64a7a46000
mmap(0x7f64a7a47000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x7000) = 0x7f64a7a47000
mmap(0x7f64a7a48000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x8000) = 0x7f64a7a48000
mmap(0x7f64a7a49000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x9000) = 0x7f64a7a49000
mmap(0x7f64a7a4a000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa000) = 0x7f64a7a4a000
mmap(0x7f64a7a4b000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xb000) = 0x7f64a7a4b000
mmap(0x7f64a7a4c000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xc000) = 0x7f64a7a4c000
mmap(0x7f64a7a4d000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xd000) = 0x7f64a7a4d000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././libglib-2.0.so.0",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\20\261\1\0\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
1568) = 1568
lseek(3, 1208776, SEEK_SET) = 1208776
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\3378yG\20\361\v\303RN\331\`\246g\2501"..., 36) =
36
fstat(3, {st_mode=S_IFREG|0755, st_size=2024688, ...}) = 0
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
1568) = 1568
mmap(NULL, 4101360, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a7450000
mprotect(0x7f64a7564000, 2932736, PROT_NONE) = 0
mmap(0x7f64a7763000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x113000) = 0x7f64a7763000
```

```
mmap(0x7f64a7765000, 2248, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64a7765000
mmap(0x7f64a7766000, 53248, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x11b000) = 0x7f64a7766000
mmap(0x7f64a7773000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x128000) = 0x7f64a7773000
mmap(0x7f64a777c000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x131000) = 0x7f64a777c000
mmap(0x7f64a7786000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x13b000) = 0x7f64a7786000
mmap(0x7f64a7790000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x145000) = 0x7f64a7790000
mmap(0x7f64a779a000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x14f000) = 0x7f64a779a000
mmap(0x7f64a77a4000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x159000) = 0x7f64a77a4000
mmap(0x7f64a77ae000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x163000) = 0x7f64a77ae000
mmap(0x7f64a77b8000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x16d000) = 0x7f64a77b8000
mmap(0x7f64a77c2000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x177000) = 0x7f64a77c2000
mmap(0x7f64a77cc000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x181000) = 0x7f64a77cc000
mmap(0x7f64a77d6000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x18b000) = 0x7f64a77d6000
mmap(0x7f64a77e0000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x195000) = 0x7f64a77e0000
mmap(0x7f64a77ea000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x19f000) = 0x7f64a77ea000
mmap(0x7f64a77f4000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1a9000) = 0x7f64a77f4000
mmap(0x7f64a77fe000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1b3000) = 0x7f64a77fe000
mmap(0x7f64a7808000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1bd000) = 0x7f64a7808000
mmap(0x7f64a7812000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1c7000) = 0x7f64a7812000
mmap(0x7f64a781c000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1d1000) = 0x7f64a781c000
mmap(0x7f64a7826000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1db000) = 0x7f64a7826000
mmap(0x7f64a7830000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1e5000) = 0x7f64a7830000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././libvtksys-8.2.so.1",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\300\300\1\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\4\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
896) = 896
lseek(3, 560416, SEEK_SET) = 560416
read(3, "\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\245{"
```



```
(No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/libxcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "x86_64/libxcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "libxcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb.so.1", O_RDONLY|O_CLOEXEC) =
3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0P\261\0\0\0\0\0"... ,
832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=162232, ...}) = 0
mmap(NULL, 2257576, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a7150000
mprotect(0x7f64a7176000, 2097152, PROT_NONE) = 0
mmap(0x7f64a7376000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x26000) = 0x7f64a7376000
close(3) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././tls/haswell/avx512_1/x86_64/libnghttp2.so.
14", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././tls/haswell/avx512_1/x86_64",
0x7fffc17b0720) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././tls/haswell/avx512_1/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././tls/haswell/avx512_1",
0x7fffc17b0720) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././tls/haswell/x86_64/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././tls/haswell/x86_64", 0x7fffc17b0720)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././tls/haswell/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././tls/haswell", 0x7fffc17b0720) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././tls/avx512_1/x86_64/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././tls/avx512_1/x86_64", 0x7fffc17b0720)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././tls/avx512_1/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././tls/avx512_1", 0x7fffc17b0720) = -1
```

```
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././tls/x86_64/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././tls/x86_64", 0x7fffc17b0720) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./././tls/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././tls", 0x7fffc17b0720) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././haswell/avx512_1/x86_64/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././haswell/avx512_1/x86_64",
0x7fffc17b0720) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././haswell/avx512_1/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././haswell/avx512_1", 0x7fffc17b0720) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././haswell/x86_64/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././haswell/x86_64", 0x7fffc17b0720) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././haswell/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././haswell", 0x7fffc17b0720) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././avx512_1/x86_64/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././avx512_1/x86_64", 0x7fffc17b0720) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././avx512_1/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././avx512_1", 0x7fffc17b0720) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./././x86_64/libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././x86_64", 0x7fffc17b0720) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./././libnghttp2.so.14",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\240L\0\0\0\0\0"... ,
832) = 832
fstat(3, {st_mode=S_IFREG|0755, st_size=694256, ...}) = 0
mmap(NULL, 2271216, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a6f20000
mprotect(0x7f64a6f45000, 2113536, PROT_NONE) = 0
mmap(0x7f64a7144000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x24000) = 0x7f64a7144000
```

```
mmap(0x7f64a7147000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa6000) = 0x7f64a7147000
mmap(0x7f64a7149000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa8000) = 0x7f64a7149000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./././libssh2.so.1",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0 t\0\0\0\0\0"..., 832)
= 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
952) = 952
fstat(3, {st_mode=S_IFREG|0755, st_size=351904, ...}) = 0
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
952) = 952
mmap(NULL, 2424480, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a6cd0000
mprotect(0x7f64a6d05000, 2199552, PROT_NONE) = 0
mmap(0x7f64a6f05000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x35000) = 0x7f64a6f05000
mmap(0x7f64a6f07000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3d000) = 0x7f64a6f07000
mmap(0x7f64a6f0a000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x40000) = 0x7f64a6f0a000
mmap(0x7f64a6f0c000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x42000) = 0x7f64a6f0c000
mmap(0x7f64a6f0e000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x44000) = 0x7f64a6f0e000
mmap(0x7f64a6f10000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x46000) = 0x7f64a6f10000
mmap(0x7f64a6f12000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x48000) = 0x7f64a6f12000
mmap(0x7f64a6f14000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4a000) = 0x7f64a6f14000
mmap(0x7f64a6f16000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4c000) = 0x7f64a6f16000
mmap(0x7f64a6f18000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4e000) = 0x7f64a6f18000
mmap(0x7f64a6f1a000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x50000) = 0x7f64a6f1a000
mmap(0x7f64a6f1c000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x52000) = 0x7f64a6f1c000
mmap(0x7f64a6f1e000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x54000) = 0x7f64a6f1e000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./././libmbdtdls.so.13",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\240}\0\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
896) = 896
fstat(3, {st_mode=S_IFREG|0755, st_size=414696, ...}) = 0
```

```
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
896) = 896
mmap(NULL, 2479080, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a6a70000
mprotect(0x7f64a6aab000, 2228224, PROT_NONE) = 0
mmap(0x7f64a6caa000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3a000) = 0x7f64a6caa000
mmap(0x7f64a6cad000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x45000) = 0x7f64a6cad000
mmap(0x7f64a6cb0000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x48000) = 0x7f64a6cb0000
mmap(0x7f64a6cb3000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4b000) = 0x7f64a6cb3000
mmap(0x7f64a6cb6000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4e000) = 0x7f64a6cb6000
mmap(0x7f64a6cb9000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x51000) = 0x7f64a6cb9000
mmap(0x7f64a6cbc000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x54000) = 0x7f64a6cbc000
mmap(0x7f64a6cbf000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x57000) = 0x7f64a6cbf000
mmap(0x7f64a6cc2000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5a000) = 0x7f64a6cc2000
mmap(0x7f64a6cc5000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5d000) = 0x7f64a6cc5000
mmap(0x7f64a6cc8000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x60000) = 0x7f64a6cc8000
mmap(0x7f64a6ccb000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x63000) = 0x7f64a6ccb000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./././libmbedx509.so.1",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\320d\0\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
840) = 840
fstat(3, {st_mode=S_IFREG|0755, st_size=279368, ...}) = 0
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x7f64a6a60000
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
840) = 840
mmap(NULL, 2351944, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a6820000
mprotect(0x7f64a6842000, 2203648, PROT_NONE) = 0
mmap(0x7f64a6a41000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x21000) = 0x7f64a6a41000
mmap(0x7f64a6a42000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x28000) = 0x7f64a6a42000
mmap(0x7f64a6a45000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2b000) = 0x7f64a6a45000
mmap(0x7f64a6a47000, 12288, PROT_READ|PROT_WRITE,
```

```
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2d000) = 0x7f64a6a47000
mmap(0x7f64a6a4a000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x30000) = 0x7f64a6a4a000
mmap(0x7f64a6a4d000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x33000) = 0x7f64a6a4d000
mmap(0x7f64a6a50000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x36000) = 0x7f64a6a50000
mmap(0x7f64a6a53000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x39000) = 0x7f64a6a53000
mmap(0x7f64a6a56000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3c000) = 0x7f64a6a56000
mmap(0x7f64a6a59000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3f000) = 0x7f64a6a59000
mmap(0x7f64a6a5c000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x42000) = 0x7f64a6a5c000
close(3)
                                = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./././libmbedcrypto.so.5",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0 #\1\0\0\0\0\0"... , 832)
= 832
fstat(3, {st_mode=S_IFREG|0755, st_size=741352, ...}) = 0
mmap(NULL, 2777064, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a6570000
mprotect(0x7f64a65ed000, 2248704, PROT_NONE) = 0
mmap(0x7f64a67ed000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x7d000) = 0x7f64a67ed000
mmap(0x7f64a67f1000, 11360, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64a67f1000
mmap(0x7f64a67f4000, 24576, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x93000) = 0x7f64a67f4000
mmap(0x7f64a67fa000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x99000) = 0x7f64a67fa000
mmap(0x7f64a67fe000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x9d000) = 0x7f64a67fe000
mmap(0x7f64a6802000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa1000) = 0x7f64a6802000
mmap(0x7f64a6806000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa5000) = 0x7f64a6806000
mmap(0x7f64a680a000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa9000) = 0x7f64a680a000
mmap(0x7f64a680e000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xad000) = 0x7f64a680e000
mmap(0x7f64a6812000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xb1000) = 0x7f64a6812000
close(3)
                                = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./././librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././lib/tls/haswell/avx512_1/x86_64/librt.so.
1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././lib/tls/haswell/avx512_1/x86_64",
0x7fffc17b0630) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././lib/tls/haswell/avx512_1/librt.so.1",
```

```
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell/avx512_1",
0x7fffc17b0630) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell/x86_64/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell/x86_64",
0x7fffc17b0630) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell", 0x7fffc17b0630) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/avx512_1/x86_64/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/avx512_1/x86_64",
0x7fffc17b0630) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/avx512_1/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/avx512_1", 0x7fffc17b0630) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/x86_64/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/x86_64", 0x7fffc17b0630) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls", 0x7fffc17b0630) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/avx512_1/x86_64/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/avx512_1/x86_64",
0x7fffc17b0630) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/avx512_1/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/avx512_1",
0x7fffc17b0630) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/x86_64/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/x86_64", 0x7fffc17b0630)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell", 0x7fffc17b0630) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/avx512_1/x86_64/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
```

```
stat("/opt/Coreform-Cubit-2021.5/bin/./././lib/avx512_1/x86_64",
0x7fffc17b0630) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././lib/avx512_1/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././lib/avx512_1", 0x7fffc17b0630) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./././lib/x86_64/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././lib/x86_64", 0x7fffc17b0630) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./././lib/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././lib", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/haswell/avx512_1/x86_64/librt.so.
1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/haswell/avx512_1/x86_64",
0x7fffc17b0630) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/haswell/avx512_1/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/haswell/avx512_1",
0x7fffc17b0630) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/haswell/x86_64/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/haswell/x86_64",
0x7fffc17b0630) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/haswell/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/haswell", 0x7fffc17b0630) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/avx512_1/x86_64/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/avx512_1/x86_64",
0x7fffc17b0630) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/avx512_1/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/avx512_1", 0x7fffc17b0630) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/x86_64/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/x86_64", 0x7fffc17b0630) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./././bin/tls/librt.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././bin/tls", 0x7fffc17b0630) = -1
ENOENT (No such file or directory)
```



```
file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libGLX.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libGLX.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libGLX.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/libGLX.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libGLX.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/libGLX.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "x86_64/libGLX.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "libGLX.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libGLX.so.0", O_RDONLY|O_CLOEXEC) =
3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\0\0\0\3\0\>\0\1\0\0\0\260/\0\0\0\0\0"...
, 832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=68144, ...}) = 0
mmap(NULL, 2295392, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a5eb0000
mprotect(0x7f64a5eb0000, 2093056, PROT_NONE) = 0
mmap(0x7f64a60bf000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xf000) = 0x7f64a60bf000
mmap(0x7f64a60c1000, 128608, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64a60c1000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libGLdispatch.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libGLdispatch.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libGLdispatch.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libGLdispatch.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libGLdispatch.so.0",
```

```
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "x86_64/libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "libGLdispatch.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libGLdispatch.so.0",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\353\3\0\0\0\0"...,
832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=612792, ...}) = 0
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x7f64a5ea0000
mmap(NULL, 2839632, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a5be0000
mprotect(0x7f64a5c4e000, 2093056, PROT_NONE) = 0
mmap(0x7f64a5e4d000, 167936, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x6d000) = 0x7f64a5e4d000
mmap(0x7f64a5e76000, 128080, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64a5e76000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/../../libpcrc.so.1",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\360\25\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
952) = 952
lseek(3, 407288, SEEK_SET) = 407288
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\234\243\321\37\1\213\356\267\31\315\263K\350\0\2
77\26"..., 36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=444472, ...}) = 0
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
952) = 952
mmap(NULL, 2537528, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a5970000
mprotect(0x7f64a59d0000, 2142208, PROT_NONE) = 0
mmap(0x7f64a5bd0000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x60000) = 0x7f64a5bd0000
mmap(0x7f64a5bd2000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x63000) = 0x7f64a5bd2000
mmap(0x7f64a5bd3000, 4096, PROT_READ|PROT_WRITE,
```

```
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x64000) = 0x7f64a5bd3000
mmap(0x7f64a5bd4000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x65000) = 0x7f64a5bd4000
mmap(0x7f64a5bd5000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x66000) = 0x7f64a5bd5000
mmap(0x7f64a5bd6000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x67000) = 0x7f64a5bd6000
mmap(0x7f64a5bd7000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x68000) = 0x7f64a5bd7000
mmap(0x7f64a5bd8000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x69000) = 0x7f64a5bd8000
mmap(0x7f64a5bd9000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x6a000) = 0x7f64a5bd9000
mmap(0x7f64a5bda000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x6b000) = 0x7f64a5bda000
mmap(0x7f64a5bdb000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x6c000) = 0x7f64a5bdb000
close(3)
= 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libXau.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libXau.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libXau.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libXau.so.6", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/x86_64/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "x86_64/libXau.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
```

```
openat(AT_FDCWD, "libXau.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libXau.so.6", O_RDONLY|O_CLOEXEC) =
3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\240\r\0\0\0\0\0"...
, 832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=14440, ...}) = 0
mmap(NULL, 2109704, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a5760000
mprotect(0x7f64a5762000, 2097152, PROT_NONE) = 0
mmap(0x7f64a5962000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2000) = 0x7f64a5962000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libXdmcp.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libXdmcp.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libXdmcp.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libXdmcp.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "x86_64/libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "libXdmcp.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file
or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libXdmcp.so.6", O_RDONLY|O_CLOEXEC)
```

```
= 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\20\21\0\0\0\0\0"...,
832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=22616, ...}) = 0
mmap(NULL, 2117760, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a5550000
mprotect(0x7f64a5550000, 2093056, PROT_NONE) = 0
mmap(0x7f64a5754000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4000) = 0x7f64a5754000
close(3) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././tls/haswell/avx512_1/x86_64/libkrb5.so.3",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././tls/haswell/avx512_1/x86_64",
0x7fffc17b04e0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././tls/haswell/avx512_1/libkrb5.so.3",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././tls/haswell/avx512_1",
0x7fffc17b04e0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././tls/haswell/x86_64/libkrb5.so.3",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././tls/haswell/x86_64",
0x7fffc17b04e0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././tls/haswell/libkrb5.so.3",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././tls/haswell", 0x7fffc17b04e0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././tls/avx512_1/x86_64/libkrb5.so.3",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././tls/avx512_1/x86_64",
0x7fffc17b04e0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././tls/avx512_1/libkrb5.so.3",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././tls/avx512_1", 0x7fffc17b04e0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././tls/x86_64/libkrb5.so.3",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././tls/x86_64", 0x7fffc17b04e0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././././tls/libkrb5.so.3",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././tls", 0x7fffc17b04e0) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././haswell/avx512_1/x86_64/libkrb5.so.3",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././haswell/avx512_1/x86_64",
0x7fffc17b04e0) = -1 ENOENT (No such file or directory)
```



```
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xfe000) = 0x7f64a552a000
mmap(0x7f64a552f000, 20480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x103000) = 0x7f64a552f000
mmap(0x7f64a5534000, 20480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x108000) = 0x7f64a5534000
mmap(0x7f64a5539000, 20480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x10d000) = 0x7f64a5539000
mmap(0x7f64a553e000, 20480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x112000) = 0x7f64a553e000
mmap(0x7f64a5543000, 24576, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x117000) = 0x7f64a5543000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././././libk5crypto.so.3",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\320H\0\0\0\0\0"... ,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"... ,
896) = 896
lseek(3, 217352, SEEK_SET) = 217352
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0_\371\321\7Z\215]b\367\177\\3451\223_\315"... ,
36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=253760, ...}) = 0
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x7f64a5220000
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"... ,
896) = 896
mmap(NULL, 2346816, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a4fe0000
mprotect(0x7f64a5011000, 2142208, PROT_NONE) = 0
mmap(0x7f64a5210000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x30000) = 0x7f64a5210000
mmap(0x7f64a5213000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x34000) = 0x7f64a5213000
mmap(0x7f64a5215000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x36000) = 0x7f64a5215000
mmap(0x7f64a5216000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x37000) = 0x7f64a5216000
mmap(0x7f64a5217000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x38000) = 0x7f64a5217000
mmap(0x7f64a5218000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x39000) = 0x7f64a5218000
mmap(0x7f64a5219000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3a000) = 0x7f64a5219000
mmap(0x7f64a521a000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3b000) = 0x7f64a521a000
mmap(0x7f64a521b000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3c000) = 0x7f64a521b000
mmap(0x7f64a521c000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3d000) = 0x7f64a521c000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././././libcom_err.so.2",
```



```
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0@\25\0\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
952) = 952
lseek(3, 17976, SEEK_SET) = 17976
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0*\335\266XF\245\f\344_\f\233b\3525\335\246"...,
36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=51064, ...}) = 0
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
952) = 952
mmap(NULL, 2148216, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a4dd0000
mprotect(0x7f64a4dd3000, 2134016, PROT_NONE) = 0
mmap(0x7f64a4fd2000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2000) = 0x7f64a4fd2000
mmap(0x7f64a4fd4000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4000) = 0x7f64a4fd4000
mmap(0x7f64a4fd5000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5000) = 0x7f64a4fd5000
mmap(0x7f64a4fd6000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x6000) = 0x7f64a4fd6000
mmap(0x7f64a4fd7000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x7000) = 0x7f64a4fd7000
mmap(0x7f64a4fd8000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x8000) = 0x7f64a4fd8000
mmap(0x7f64a4fd9000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x9000) = 0x7f64a4fd9000
mmap(0x7f64a4fda000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xa000) = 0x7f64a4fda000
mmap(0x7f64a4fdb000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xb000) = 0x7f64a4fdb000
mmap(0x7f64a4fdc000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xc000) = 0x7f64a4fdc000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././././libkrb5support.so.0",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\360;\0\0\0\0\0"...,
832) = 832
lseek(3, 74264, SEEK_SET) = 74264
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0w\223\201\6=\256\314'\350H\f\217y\360e\21"...,
36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=94016, ...}) = 0
mmap(NULL, 2187072, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a4bb0000
mprotect(0x7f64a4bbe000, 2125824, PROT_NONE) = 0
mmap(0x7f64a4dbe000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xe000) = 0x7f64a4dbe000
mmap(0x7f64a4dc0000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x11000) = 0x7f64a4dc0000
```

```
mmap(0x7f64a4dc2000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x13000) = 0x7f64a4dc2000
mmap(0x7f64a4dc3000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x14000) = 0x7f64a4dc3000
mmap(0x7f64a4dc4000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x15000) = 0x7f64a4dc4000
mmap(0x7f64a4dc5000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x16000) = 0x7f64a4dc5000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././././libkeyutils.so.1",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\260\25\0\0\0\0\0"...
, 832) = 832
lseek(3, 18416, SEEK_SET) = 18416
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0.\1\325\254\10\301(\r\1:\253\226\262\222\254X"...
, 36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=34648, ...}) = 0
mmap(NULL, 2131800, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a49a0000
mprotect(0x7f64a49a3000, 2117632, PROT_NONE) = 0
mmap(0x7f64a4ba2000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2000) = 0x7f64a4ba2000
mmap(0x7f64a4ba4000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4000) = 0x7f64a4ba4000
mmap(0x7f64a4ba5000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x5000) = 0x7f64a4ba5000
mmap(0x7f64a4ba6000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x6000) = 0x7f64a4ba6000
mmap(0x7f64a4ba7000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x7000) = 0x7f64a4ba7000
mmap(0x7f64a4ba8000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x8000) = 0x7f64a4ba8000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././././libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell/avx512_1/x86_64/libreso
lv.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell/avx512_1/x86_64",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell/avx512_1/libresolv.so.2
", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell/avx512_1",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell/x86_64/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell/x86_64",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
```

```
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/haswell", 0x7fffc17b03f0)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/avx512_1/x86_64/libresolv.so.2"
, O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/avx512_1/x86_64",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/avx512_1/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/avx512_1", 0x7fffc17b03f0)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/x86_64/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/x86_64", 0x7fffc17b03f0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/tls/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/tls", 0x7fffc17b03f0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/avx512_1/x86_64/libresolv.s
o.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/avx512_1/x86_64",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/avx512_1/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/avx512_1",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/x86_64/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/x86_64",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/haswell", 0x7fffc17b03f0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/avx512_1/x86_64/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/avx512_1/x86_64",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/avx512_1/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib/avx512_1", 0x7fffc17b03f0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././lib/x86_64/libresolv.so.2",
```

```
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././././lib/x86_64", 0x7fffc17b03f0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././././lib/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././lib", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/haswell/avx512_1/x86_64/libreso
lv.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/haswell/avx512_1/x86_64",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/haswell/avx512_1/libresolv.so.2
", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/haswell/avx512_1",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/haswell/x86_64/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/haswell/x86_64",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/haswell/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/haswell", 0x7fffc17b03f0)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/avx512_1/x86_64/libresolv.so.2"
, O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/avx512_1/x86_64",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/avx512_1/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/avx512_1", 0x7fffc17b03f0)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/x86_64/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/x86_64", 0x7fffc17b03f0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/tls/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/tls", 0x7fffc17b03f0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/haswell/avx512_1/x86_64/libresolv.s
o.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/haswell/avx512_1/x86_64",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/haswell/avx512_1/libresolv.so.2",
```

```
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/haswell/avx512_1",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/haswell/x86_64/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/haswell/x86_64",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/haswell/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/haswell", 0x7fffc17b03f0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/avx512_1/x86_64/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/avx512_1/x86_64",
0x7fffc17b03f0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/avx512_1/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/avx512_1", 0x7fffc17b03f0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/././././bin/x86_64/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin/x86_64", 0x7fffc17b03f0) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/././././bin/libresolv.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/././././bin", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/lib/x86_64-linux-gnu/libresolv.so.2", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\0\0\0\0\3\0\>\0\1\0\0\00008\0\0\0\0\0"...,
832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=97072, ...}) = 0
mmap(NULL, 2202240, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a4780000
mprotect(0x7f64a4797000, 2093056, PROT_NONE) = 0
mmap(0x7f64a4996000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x16000) = 0x7f64a4996000
mmap(0x7f64a4998000, 6784, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64a4998000
close(3) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libbsd.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libbsd.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libbsd.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libbsd.so.0", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libbsd.so.0", O_RDONLY|O_CLOEXEC) = -1
```



```
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../../../tls/haswell/x86_64/libselinux.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../../../tls/haswell/x86_64",
0x7fffc17b0390) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../../../tls/haswell/libselinux.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../../../tls/haswell", 0x7fffc17b0390) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../../../tls/avx512_1/x86_64/libselinux.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../../../tls/avx512_1/x86_64",
0x7fffc17b0390) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../../../tls/avx512_1/libselinux.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../../../tls/avx512_1", 0x7fffc17b0390) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../../../tls/x86_64/libselinux.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../../../tls/x86_64", 0x7fffc17b0390) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/../../../../tls/libselinux.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../../../tls", 0x7fffc17b0390) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../../../haswell/avx512_1/x86_64/libselinux.so.
1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../../../haswell/avx512_1/x86_64",
0x7fffc17b0390) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../../../haswell/avx512_1/libselinux.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../../../haswell/avx512_1",
0x7fffc17b0390) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../../../haswell/x86_64/libselinux.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../../../haswell/x86_64", 0x7fffc17b0390)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../../../haswell/libselinux.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../../../haswell", 0x7fffc17b0390) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/../../../../avx512_1/x86_64/libselinux.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/../../../../avx512_1/x86_64", 0x7fffc17b0390)
= -1 ENOENT (No such file or directory)
```

```
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././././avx512_1/libselinux.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././././avx512_1", 0x7fffc17b0390) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./././././x86_64/libselinux.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/./././././x86_64", 0x7fffc17b0390) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./././././libselinux.so.1",
O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\220j\0\0\0\0\0"...,
832) = 832
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
840) = 840
lseek(3, 168584, SEEK_SET) = 168584
read(3,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\220:\v\320\277\264\376\350\302\204\364\33\353\22
7s\336"..., 36) = 36
fstat(3, {st_mode=S_IFREG|0755, st_size=220176, ...}) = 0
lseek(3, 64, SEEK_SET) = 64
read(3, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
840) = 840
mmap(NULL, 2317328, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x7f64a4310000
mprotect(0x7f64a4334000, 2162688, PROT_NONE) = 0
mmap(0x7f64a4533000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x23000) = 0x7f64a4533000
mmap(0x7f64a4535000, 6512, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64a4535000
mmap(0x7f64a4537000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x27000) = 0x7f64a4537000
mmap(0x7f64a453a000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2a000) = 0x7f64a453a000
mmap(0x7f64a453c000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2c000) = 0x7f64a453c000
mmap(0x7f64a453e000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2e000) = 0x7f64a453e000
mmap(0x7f64a4540000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x30000) = 0x7f64a4540000
mmap(0x7f64a4542000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x32000) = 0x7f64a4542000
mmap(0x7f64a4544000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x34000) = 0x7f64a4544000
close(3) = 0
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x7f64a4300000
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x7f64a42f0000
mmap(NULL, 12288, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x7f64a42e0000
arch_prctl(ARCH_SET_FS, 0x7f64a42e0900) = 0
```



```
mprotect(0x7f64acfa7000, 16384, PROT_READ) = 0
mprotect(0x7f64ad792000, 4096, PROT_READ) = 0
mprotect(0x7f64b49f9000, 4096, PROT_READ) = 0
mprotect(0x7f64a5bd0000, 4096, PROT_READ) = 0
mprotect(0x7f64a4533000, 4096, PROT_READ) = 0
mprotect(0x7f64a6566000, 4096, PROT_READ) = 0
mprotect(0x7f64a4762000, 4096, PROT_READ) = 0
mprotect(0x7f64a4996000, 4096, PROT_READ) = 0
mprotect(0x7f64a4ba2000, 4096, PROT_READ) = 0
mprotect(0x7f64a4dbe000, 4096, PROT_READ) = 0
mprotect(0x7f64a4fd2000, 4096, PROT_READ) = 0
mprotect(0x7f64a5210000, 8192, PROT_READ) = 0
mprotect(0x7f64a5508000, 57344, PROT_READ) = 0
mprotect(0x7f64a5754000, 4096, PROT_READ) = 0
mprotect(0x7f64a5962000, 4096, PROT_READ) = 0
mprotect(0x7f64a5e4d000, 163840, PROT_READ) = 0
mprotect(0x7f64a7376000, 4096, PROT_READ) = 0
mprotect(0x7f64adad3000, 4096, PROT_READ) = 0
mprotect(0x7f64a60bf000, 4096, PROT_READ) = 0
mprotect(0x7f64a633a000, 4096, PROT_READ) = 0
mprotect(0x7f64ad35c000, 4096, PROT_READ) = 0
mprotect(0x7f64b4b1b000, 4096, PROT_READ) = 0
mprotect(0x7f64ad52f000, 45056, PROT_READ) = 0
mprotect(0x7f64a73da000, 4096, PROT_READ) = 0
mprotect(0x7f64a7763000, 4096, PROT_READ) = 0
mprotect(0x7f64a7a40000, 4096, PROT_READ) = 0
mprotect(0x7f64a9432000, 4096, PROT_READ) = 0
mprotect(0x7f64aafc5000, 65536, PROT_READ) = 0
mprotect(0x7f64ab548000, 57344, PROT_READ) = 0
mprotect(0x7f64aba24000, 4096, PROT_READ) = 0
mprotect(0x7f64abcd0000, 106496, PROT_READ) = 0
mprotect(0x7f64ae884000, 53248, PROT_READ) = 0
mprotect(0x7f64ac094000, 24576, PROT_READ) = 0
mprotect(0x7f64aca6c000, 16384, PROT_READ) = 0
mprotect(0x7f64b4a7b000, 12288, PROT_READ) = 0
mprotect(0x7f64b0f5f000, 77824, PROT_READ) = 0
mprotect(0x7f64b3e7f000, 188416, PROT_READ) = 0
mprotect(0x7f64b4ad8000, 8192, PROT_READ) = 0
mprotect(0x7f64adeda000, 122880, PROT_READ) = 0
mprotect(0x7f64b47af000, 16384, PROT_READ) = 0
mprotect(0x7f64b4caa000, 12288, PROT_READ) = 0
mprotect(0x7f64b4bdb000, 20480, PROT_READ) = 0
mprotect(0x451000, 12288, PROT_READ) = 0
mprotect(0x7f64b4c29000, 4096, PROT_READ) = 0
munmap(0x7f64b4cd5000, 41866) = 0
set_tid_address(0x7f64a42e0bd0) = 175
set_robust_list(0x7f64a42e0be0, 24) = 0
rt_sigaction(SIGRTMIN, {sa_handler=0x7f64b47e5cb0, sa_mask=[],
sa_flags=SA_RESTORER|SA_SIGINFO, sa_restorer=0x7f64b47f2980}, NULL, 8) = 0
rt_sigaction(SIGRT_1, {sa_handler=0x7f64b47e5d50, sa_mask=[],
sa_flags=SA_RESTORER|SA_RESTART|SA_SIGINFO, sa_restorer=0x7f64b47f2980}, NULL,
8) = 0
rt_sigprocmask(SIG_UNBLOCK, [RTMIN RT_1], NULL, 8) = 0
prlimit64(0, RLIMIT_STACK, NULL, {rlim_cur=8192*1024, rlim_max=8192*1024}) = 0
```



```
4096) = 1719
close(4) = 0
fstat(3, {st_mode=S_IFREG|0644, st_size=10476, ...}) = 0
write(3, "[2021-10-18 16:34:51.179] [app_1"... , 56) = 56
socket(AF_UNIX, SOCK_STREAM|SOCK_CLOEXEC, 0) = 4
connect(4, {sa_family=AF_UNIX, sun_path="@/tmp/.X11-unix/X0"}, 20) = -1
ECONNREFUSED (Connection refused)
close(4) = 0
socket(AF_UNIX, SOCK_STREAM|SOCK_CLOEXEC, 0) = 4
getsockopt(4, SOL_SOCKET, SO_SNDBUF, [0], [4]) = 0
setsockopt(4, SOL_SOCKET, SO_SNDBUF, [65536], 4) = 0
connect(4, {sa_family=AF_UNIX, sun_path="/tmp/.X11-unix/X0"}, 110) = -1 ENOENT
(No such file or directory)
close(4) = 0
socket(AF_UNIX, SOCK_STREAM|SOCK_CLOEXEC|SOCK_NONBLOCK, 0) = 4
connect(4, {sa_family=AF_UNIX, sun_path="/var/run/nscd/socket"}, 110) = -1
ENOENT (No such file or directory)
close(4) = 0
socket(AF_UNIX, SOCK_STREAM|SOCK_CLOEXEC|SOCK_NONBLOCK, 0) = 4
connect(4, {sa_family=AF_UNIX, sun_path="/var/run/nscd/socket"}, 110) = -1
ENOENT (No such file or directory)
close(4) = 0
openat(AT_FDCWD, "/etc/nsswitch.conf", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=513, ...}) = 0
read(4, "# /etc/nsswitch.conf\n#\n# Example"... , 4096) = 513
read(4, "", 4096) = 0
close(4) = 0
stat("/etc/resolv.conf", {st_mode=S_IFREG|0644, st_size=218, ...}) = 0
openat(AT_FDCWD, "/etc/host.conf", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=92, ...}) = 0
read(4, "# The \"order\" line is only used "... , 4096) = 92
read(4, "", 4096) = 0
close(4) = 0
futext(0x7f64acfafba4, FUTEX_WAKE_PRIVATE, 2147483647) = 0
openat(AT_FDCWD, "/etc/resolv.conf", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=218, ...}) = 0
read(4, "# This file was automatically ge"... , 4096) = 218
read(4, "", 4096) = 0
close(4) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libnss_files.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libnss_files.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libnss_files.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libnss_files.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libnss_files.so.2", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libnss_files.so.2", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libnss_files.so.2", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libnss_files.so.2", O_RDONLY|O_CLOEXEC) =
```



```
clock_gettime(CLOCK_REALTIME, {tv_sec=1634567691, tv_nsec=185019200}) = 0
write(3, "[2021-10-18 16:34:51.185] [app_1"... , 69) = 69
clock_gettime(CLOCK_REALTIME, {tv_sec=1634567691, tv_nsec=185123900}) = 0
write(3, "[2021-10-18 16:34:51.185] [app_1"... , 82) = 82
access("/opt/Coreform-Cubit-2021.5/lib", F_OK) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/qtlogging.ini", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
stat("/home/lovepreet/.config/QtProject/qtlogging.ini", 0x7fffc17b1f00) = -1
ENOENT (No such file or directory)
stat("/etc/xdg/QtProject/qtlogging.ini", 0x7fffc17b1f00) = -1 ENOENT (No such
file or directory)
geteuid() = 1000
getuid() = 1000
openat(AT_FDCWD, "/usr/lib/locale/locale-archive", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=1683056, ...}) = 0
mmap(NULL, 1683056, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64a3f25000
close(4) = 0
openat(AT_FDCWD, "/usr/share/locale/locale.alias", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=2995, ...}) = 0
read(4, "# Locale name alias data base.\n#"..., 4096) = 2995
read(4, "", 4096) = 0
close(4) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_IDENTIFICATION",
O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=252, ...}) = 0
mmap(NULL, 252, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64b4ce9000
close(4) = 0
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/gconv/gconv-modules.cache",
O_RDONLY) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=26376, ...}) = 0
mmap(NULL, 26376, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64b4ce2000
close(4) = 0
futext(0x7f64acfaca08, FUTEX_WAKE_PRIVATE, 2147483647) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_MEASUREMENT", O_RDONLY|O_CLOEXEC) =
4
fstat(4, {st_mode=S_IFREG|0644, st_size=23, ...}) = 0
mmap(NULL, 23, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64b4cdf000
close(4) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_TELEPHONE", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=47, ...}) = 0
mmap(NULL, 47, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64b4cde000
close(4) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_ADDRESS", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=131, ...}) = 0
mmap(NULL, 131, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64b4cdd000
close(4) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_NAME", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=62, ...}) = 0
mmap(NULL, 62, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64b4cdc000
close(4) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_PAPER", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=34, ...}) = 0
mmap(NULL, 34, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64b4cdb000
close(4) = 0
```

```
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_MESSAGES", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
close(4) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_MESSAGES/SYS_LC_MESSAGES",
O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=48, ...}) = 0
mmap(NULL, 48, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64b4cda000
close(4) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_MONETARY", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=270, ...}) = 0
mmap(NULL, 270, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64b4cd9000
close(4) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_COLLATE", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=1516558, ...}) = 0
mmap(NULL, 1516558, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64a3db2000
close(4) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_TIME", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=3360, ...}) = 0
mmap(NULL, 3360, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64b4cd8000
close(4) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_NUMERIC", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=50, ...}) = 0
mmap(NULL, 50, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64b4cd7000
close(4) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_CTYPE", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=199772, ...}) = 0
mmap(NULL, 199772, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64a3d81000
close(4) = 0
getpid() = 175
access("/proc/175/exe", F_OK) = 0
lstat("/proc/175/exe", {st_mode=S_IFLNK|0777, st_size=0, ...}) = 0
lstat("/proc", {st_mode=S_IFDIR|0555, st_size=0, ...}) = 0
lstat("/proc/175", {st_mode=S_IFDIR|0555, st_size=0, ...}) = 0
lstat("/proc/175/exe", {st_mode=S_IFLNK|0777, st_size=0, ...}) = 0
readlink("/proc/175/exe", "/opt/Coreform-Cubit-2021.5/bin/c"..., 4095) = 45
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/coreform_cubit", {st_mode=S_IFREG|0755,
st_size=354072, ...}) = 0
access("/opt/Coreform-Cubit-2021.5/bin/qt.conf", F_OK) = 0
access("/opt/Coreform-Cubit-2021.5/bin/qt.conf", F_OK) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/qt.conf", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0664, st_size=0, ...}) = 0
fstat(4, {st_mode=S_IFREG|0664, st_size=0, ...}) = 0
stat("/opt/Coreform-Cubit-2021.5/bin/qt.conf", {st_mode=S_IFREG|0664, st_size=0,
...}) = 0
stat("/etc/localtime", {st_mode=S_IFREG|0644, st_size=2692, ...}) = 0
stat("/etc/localtime", {st_mode=S_IFREG|0644, st_size=2692, ...}) = 0
stat("/etc/localtime", {st_mode=S_IFREG|0644, st_size=2692, ...}) = 0
close(4) = 0
```

```
access("/opt/Coreform-Cubit-2021.5/bin/plugins", F_OK) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
access("/opt/Coreform-Cubit-2021.5/bin", F_OK) = 0
access("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/.", F_OK) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/plugins/platforms",
O_RDONLY|O_NONBLOCK|O_CLOEXEC|O_DIRECTORY) = 4
fstat(4, {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
getdents(4, /* 21 entries */, 32768) = 824
getdents(4, /* 0 entries */, 32768) = 0
close(4) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libdrm.so.2",
{st_mode=S_IFREG|0755, st_size=102896, ...}) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libdrm.so.2",
O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=102896, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=102896, ...}) = 0
mmap(NULL, 102896, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3d67000
close(4) = 0
munmap(0x7f64a3d67000, 102896) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libEGL.so.1",
{st_mode=S_IFREG|0755, st_size=101000, ...}) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libEGL.so.1",
O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=101000, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=101000, ...}) = 0
```

```
mmap(NULL, 101000, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3d68000
close(4) = 0
munmap(0x7f64a3d68000, 101000) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libffi.so.6",
{st_mode=S_IFREG|0755, st_size=46880, ...}) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libffi.so.6",
O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=46880, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=46880, ...}) = 0
mmap(NULL, 46880, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64b4c34000
close(4) = 0
munmap(0x7f64b4c34000, 46880) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libGLdispatch.so.0",
{st_mode=S_IFREG|0755, st_size=657048, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libGLdispatch.so.0",
O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=657048, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=657048, ...}) = 0
mmap(NULL, 657048, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3ce0000
close(4) = 0
munmap(0x7f64a3ce0000, 657048) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqeglfs.so",
{st_mode=S_IFREG|0755, st_size=31208, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqeglfs.so",
O_RDONLY|O_CLOEXEC) = 4
```



```
fstat(4, {st_mode=S_IFREG|0755, st_size=31208, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=31208, ...}) = 0
mmap(NULL, 31208, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64b4cc8000
close(4) = 0
munmap(0x7f64b4cc8000, 31208) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqlinuxfb.so", {st_mode=S_IFREG|0755, st_size=719312, ...}) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqlinuxfb.so", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=719312, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=719312, ...}) = 0
mmap(NULL, 719312, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3cd1000
close(4) = 0
munmap(0x7f64a3cd1000, 719312) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqminimal.so", {st_mode=S_IFREG|0755, st_size=279032, ...}) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqminimal.so", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=279032, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=279032, ...}) = 0
mmap(NULL, 279032, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3d3c000
close(4) = 0
munmap(0x7f64a3d3c000, 279032) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqminimalegl.so", {st_mode=S_IFREG|0755, st_size=344832, ...}) = 0
```

```
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqminimalegl.so",
O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=344832, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=344832, ...}) = 0
mmap(NULL, 344832, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3d2c000
close(4) = 0
munmap(0x7f64a3d2c000, 344832) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqoffscreen.so",
{st_mode=S_IFREG|0755, st_size=372464, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqoffscreen.so",
O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=372464, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=372464, ...}) = 0
mmap(NULL, 372464, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3d26000
close(4) = 0
munmap(0x7f64a3d26000, 372464) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libQt5EglFSDeviceIntegra
tion.so.5", {st_mode=S_IFREG|0755, st_size=1179976, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libQt5EglFSDeviceIntegra
tion.so.5", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=1179976, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=1179976, ...}) = 0
mmap(NULL, 1179976, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3c60000
close(4) = 0
munmap(0x7f64a3c60000, 1179976) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
```

```
st_size=4096, ...) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libQt5WaylandClient.so.5", {st_mode=S_IFREG|0755, st_size=2542016, ...}) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libQt5WaylandClient.so.5", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=2542016, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=2542016, ...}) = 0
mmap(NULL, 2542016, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3b14000
close(4) = 0
munmap(0x7f64a3b14000, 2542016) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqvinc.so", {st_mode=S_IFREG|0755, st_size=469256, ...}) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqvinc.so", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=469256, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=469256, ...}) = 0
mmap(NULL, 469256, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3d0e000
close(4) = 0
munmap(0x7f64a3d0e000, 469256) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqwayland-egl.so", {st_mode=S_IFREG|0755, st_size=173384, ...}) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqwayland-egl.so", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=173384, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=173384, ...}) = 0
mmap(NULL, 173384, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3d56000
close(4) = 0
munmap(0x7f64a3d56000, 173384) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
```

```
st_size=4096, ...) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqwayland-generic.so",
{st_mode=S_IFREG|0755, st_size=31040, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqwayland-generic.so",
O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=31040, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=31040, ...}) = 0
mmap(NULL, 31040, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64b4cc8000
close(4) = 0
munmap(0x7f64b4cc8000, 31040) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqwayland-xcomposite-e
gl.so", {st_mode=S_IFREG|0755, st_size=176784, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqwayland-xcomposite-egl.so"
, O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=176784, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=176784, ...}) = 0
mmap(NULL, 176784, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3d55000
close(4) = 0
munmap(0x7f64a3d55000, 176784) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqwayland-xcomposite-g
lx.so", {st_mode=S_IFREG|0755, st_size=142880, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqwayland-xcomposite-glx.so"
, O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=142880, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=142880, ...}) = 0
mmap(NULL, 142880, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3d5e000
close(4) = 0
munmap(0x7f64a3d5e000, 142880) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
```

```
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqwebgl.so",
{st_mode=S_IFREG|0755, st_size=1297064, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqwebgl.so",
O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=1297064, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=1297064, ...}) = 0
mmap(NULL, 1297064, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3c44000
close(4) = 0
munmap(0x7f64a3c44000, 1297064) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqxcb.so",
{st_mode=S_IFREG|0755, st_size=31680, ...}) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqxcb.so",
O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=31680, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=31680, ...}) = 0
mmap(NULL, 31680, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64b4cc8000
close(4) = 0
munmap(0x7f64b4cc8000, 31680) = 0
lstat("/opt", {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5", {st_mode=S_IFDIR|0775, st_size=4096, ...}) =
0
lstat("/opt/Coreform-Cubit-2021.5/bin", {st_mode=S_IFDIR|0775, st_size=4096,
...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms", {st_mode=S_IFDIR|0775,
st_size=4096, ...}) = 0
lstat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libwayland-client.so.0",
{st_mode=S_IFREG|0755, st_size=81040, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libwayland-client.so.0",
O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0755, st_size=81040, ...}) = 0
fstat(4, {st_mode=S_IFREG|0755, st_size=81040, ...}) = 0
mmap(NULL, 81040, PROT_READ, MAP_SHARED, 4, 0) = 0x7f64a3d6d000
close(4) = 0
munmap(0x7f64a3d6d000, 81040) = 0
access("/opt/Coreform-Cubit-2021.5/bin/platforms/.", F_OK) = -1 ENOENT (No such
```

```
file or directory)
access("/opt/Coreform-Cubit-2021.5/bin/qt.conf", F_OK) = 0
access("/opt/Coreform-Cubit-2021.5/bin/qt.conf", F_OK) = 0
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/qt.conf", O_RDONLY|O_CLOEXEC) =
4
fstat(4, {st_mode=S_IFREG|0664, st_size=0, ...}) = 0
fstat(4, {st_mode=S_IFREG|0664, st_size=0, ...}) = 0
stat("/opt/Coreform-Cubit-2021.5/bin/qt.conf", {st_mode=S_IFREG|0664, st_size=0,
...}) = 0
stat("/etc/localtime", {st_mode=S_IFREG|0644, st_size=2692, ...}) = 0
stat("/etc/localtime", {st_mode=S_IFREG|0644, st_size=2692, ...}) = 0
stat("/etc/localtime", {st_mode=S_IFREG|0644, st_size=2692, ...}) = 0
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqxcb.so.avx2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
access("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqxcb.so.avx2", F_OK)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/libqxcb.so",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0\>\0\1\0\0\0\0\24\0\0\0\0\0"...,
832) = 832
lseek(4, 20272, SEEK_SET) = 20272
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0$\36(\3411\274\34'\377\207G\224\212\260\251\327".
.., 36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=31680, ...}) = 0
mmap(NULL, 2124736, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a3b70000
mprotect(0x7f64a3b72000, 2113536, PROT_NONE) = 0
mmap(0x7f64a3d71000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1000) = 0x7f64a3d71000
mmap(0x7f64a3d73000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x4000) = 0x7f64a3d73000
mmap(0x7f64a3d74000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x5000) = 0x7f64a3d74000
mmap(0x7f64a3d75000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x6000) = 0x7f64a3d75000
mmap(0x7f64a3d76000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x7000) = 0x7f64a3d76000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/haswell/avx512_1/x86_64/
libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/haswell/avx512_1/x8
6_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/haswell/avx512_1/libQt5X
cbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/haswell/avx512_1",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/haswell/x86_64/libQt5Xcb
Qpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
```

```
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/haswell/x86_64",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/haswell/libQt5XcbQpa.so.
5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/haswell",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/avx512_1/x86_64/libQt5Xc
bQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/avx512_1/x86_64",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/avx512_1/libQt5XcbQpa.so
.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/avx512_1",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/x86_64/libQt5XcbQpa.so.5
", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/x86_64",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls/libQt5XcbQpa.so.5",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./tls", 0x7fffc17b0dc0) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./haswell/avx512_1/x86_64/libQ
t5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./haswell/avx512_1/x86_64
", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./haswell/avx512_1/libQt5XcbQp
a.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./haswell/avx512_1",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./haswell/x86_64/libQt5XcbQpa.
so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./haswell/x86_64",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./haswell/libQt5XcbQpa.so.5",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./haswell",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./avx512_1/x86_64/libQt5XcbQpa
.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./avx512_1/x86_64",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./avx512_1/libQt5XcbQpa.so.5",
```

```
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./avx512_1",
0x7ffffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./x86_64/libQt5XcbQpa.so.5",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./x86_64",
0x7ffffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libQt5XcbQpa.so.5",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/.",
{st_mode=S_IFDIR|0775, st_size=4096, ...}) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/haswell/avx512_1/x8
6_64/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/haswell/avx512
_1/x86_64", 0x7ffffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/haswell/avx512_1/li
bQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/haswell/avx512
_1", 0x7ffffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/haswell/x86_64/libQ
t5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/haswell/x86_64
", 0x7ffffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/haswell/libQt5XcbQp
a.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/haswell",
0x7ffffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/avx512_1/x86_64/lib
Qt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/avx512_1/x86_6
4", 0x7ffffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/avx512_1/libQt5XcbQ
pa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/avx512_1",
0x7ffffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/x86_64/libQt5XcbQpa
.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/x86_64",
0x7ffffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls/libQt5XcbQpa.so.5",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/tls",
0x7ffffc17b0dc0) = -1 ENOENT (No such file or directory)
```



```
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/haswell/avx512_1/x86_64
/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/haswell/avx512_1/x
86_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/haswell/avx512_1/libQt5
XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/haswell/avx512_1",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/haswell/x86_64/libQt5Xc
bQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/haswell/x86_64",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/haswell/libQt5XcbQpa.so
.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/haswell",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/avx512_1/x86_64/libQt5X
cbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/avx512_1/x86_64",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/avx512_1/libQt5XcbQpa.s
o.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/avx512_1",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/x86_64/libQt5XcbQpa.so.
5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/x86_64",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib/libQt5XcbQpa.so.5",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./lib", 0x7fffc17b0dc0)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/haswell/avx512_1/x8
6_64/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/haswell/avx512
_1/x86_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/haswell/avx512_1/li
bQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/haswell/avx512
_1", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/haswell/x86_64/libQ
t5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
```

```
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/haswell/x86_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/haswell/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/haswell", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/avx512_1/x86_64/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/avx512_1/x86_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/avx512_1/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/avx512_1", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/x86_64/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/x86_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/tls", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/haswell/avx512_1/x86_64/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/haswell/avx512_1/x86_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/haswell/avx512_1/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/haswell/avx512_1", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/haswell/x86_64/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/haswell/x86_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/haswell/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/haswell", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/avx512_1/x86_64/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/avx512_1/x86_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/avx512_1/libQt5XcbQpa.s
```

```
o.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/avx512_1",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/x86_64/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/x86_64",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin/libQt5XcbQpa.so.5",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./bin", 0x7fffc17b0dc0)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/haswell/avx512_1/x86_64/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/haswell/avx512_1/x86_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/haswell/avx512_1/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/haswell/avx512_1", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/haswell/x86_64/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/haswell/x86_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/haswell/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/haswell", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/avx512_1/x86_64/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/avx512_1/x86_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/avx512_1/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/avx512_1", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/x86_64/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/x86_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls/libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./../tls", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
```

```
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../haswell/avx512_1/x86_64/
libQt5XcbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../haswell/avx512_1/x8
6_64", 0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../haswell/avx512_1/libQt5X
cbQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../haswell/avx512_1",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../haswell/x86_64/libQt5Xcb
Qpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../haswell/x86_64",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../haswell/libQt5XcbQpa.so.
5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../haswell",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../avx512_1/x86_64/libQt5Xc
bQpa.so.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../avx512_1/x86_64",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../avx512_1/libQt5XcbQpa.so
.5", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../avx512_1",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../x86_64/libQt5XcbQpa.so.5
", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../x86_64",
0x7fffc17b0dc0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libQt5XcbQpa.so.5",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0\>\0\1\0\0\0\0v\3\0\0\0\0\0"... , 832)
= 832
lseek(4, 64, SEEK_SET) = 64
read(4, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"... ,
840) = 840
lseek(4, 1869344, SEEK_SET) = 1869344
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0A\321~\271\342\370\303\245v2\205;>A\371\345"... ,
36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=2386792, ...}) = 0
lseek(4, 64, SEEK_SET) = 64
read(4, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"... ,
840) = 840
mmap(NULL, 4098920, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a3780000
mprotect(0x7f64a38ce000, 2658304, PROT_NONE) = 0
```

```
mmap(0x7f64a3acd000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x14d000) = 0x7f64a3acd000
mmap(0x7f64a3ad6000, 5360, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64a3ad6000
mmap(0x7f64a3ad8000, 77824, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1b6000) = 0x7f64a3ad8000
mmap(0x7f64a3aeb000, 73728, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1c9000) = 0x7f64a3aeb000
mmap(0x7f64a3afd000, 73728, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1db000) = 0x7f64a3afd000
mmap(0x7f64a3b0f000, 73728, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1ed000) = 0x7f64a3b0f000
mmap(0x7f64a3b21000, 73728, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1ff000) = 0x7f64a3b21000
mmap(0x7f64a3b33000, 73728, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x211000) = 0x7f64a3b33000
mmap(0x7f64a3b45000, 73728, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x223000) = 0x7f64a3b45000
mmap(0x7f64a3b57000, 73728, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x235000) = 0x7f64a3b57000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libfontconfig.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libfontconfig.so.1",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\360q\0\0\0\0\0"...,
832) = 832
lseek(4, 64, SEEK_SET) = 64
read(4, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
1344) = 1344
lseek(4, 286648, SEEK_SET) = 286648
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\365\5'K\v\216m\316\250VA\202p8\212\25"..., 36) =
36
fstat(4, {st_mode=S_IFREG|0755, st_size=416784, ...}) = 0
lseek(4, 64, SEEK_SET) = 64
read(4, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
1344) = 1344
mmap(NULL, 2505744, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a3510000
mprotect(0x7f64a3550000, 2236416, PROT_NONE) = 0
mmap(0x7f64a374f000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x3f000) = 0x7f64a374f000
mmap(0x7f64a3752000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x44000) = 0x7f64a3752000
mmap(0x7f64a3754000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x46000) = 0x7f64a3754000
mmap(0x7f64a3756000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x48000) = 0x7f64a3756000
mmap(0x7f64a3758000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x4a000) = 0x7f64a3758000
mmap(0x7f64a375a000, 8192, PROT_READ|PROT_WRITE,
```



```
mmap(0x7f64a34c8000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xcc000) = 0x7f64a34c8000
mmap(0x7f64a34cc000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xd0000) = 0x7f64a34cc000
mmap(0x7f64a34d0000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xd4000) = 0x7f64a34d0000
mmap(0x7f64a34d4000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xd8000) = 0x7f64a34d4000
mmap(0x7f64a34d8000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xdc000) = 0x7f64a34d8000
mmap(0x7f64a34dc000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xe0000) = 0x7f64a34dc000
mmap(0x7f64a34e0000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xe4000) = 0x7f64a34e0000
mmap(0x7f64a34e4000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xe8000) = 0x7f64a34e4000
mmap(0x7f64a34e8000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xec000) = 0x7f64a34e8000
mmap(0x7f64a34ec000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xf0000) = 0x7f64a34ec000
mmap(0x7f64a34f0000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xf4000) = 0x7f64a34f0000
mmap(0x7f64a34f4000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xf8000) = 0x7f64a34f4000
mmap(0x7f64a34f8000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xfc000) = 0x7f64a34f8000
mmap(0x7f64a34fc000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x100000) = 0x7f64a34fc000
mmap(0x7f64a3500000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x104000) = 0x7f64a3500000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libQt5DBus.so.5",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libQt5DBus.so.5",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\0\3\0\>\0\1\0\0\0\340Y\1\0\0\0\0"...,
832) = 832
lseek(4, 64, SEEK_SET) = 64
read(4, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
2576) = 2576
lseek(4, 790496, SEEK_SET) = 790496
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0#8\317\0\322\203\375\300~\0\17z\355\3\0\0\371"...,
36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=2194416, ...}) = 0
lseek(4, 64, SEEK_SET) = 64
read(4, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
2576) = 2576
mmap(NULL, 4111344, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a2e10000
mprotect(0x7f64a2e99000, 3514368, PROT_NONE) = 0
mmap(0x7f64a3098000, 12288, PROT_READ|PROT_WRITE,
```

MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x88000) = 0x7f64a3098000
mmap(0x7f64a309b000, 920, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64a309b000
mmap(0x7f64a309c000, 40960, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xb8000) = 0x7f64a309c000
mmap(0x7f64a30a6000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xc2000) = 0x7f64a30a6000
mmap(0x7f64a30af000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xcb000) = 0x7f64a30af000
mmap(0x7f64a30b8000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xd4000) = 0x7f64a30b8000
mmap(0x7f64a30c1000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xdd000) = 0x7f64a30c1000
mmap(0x7f64a30ca000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xe6000) = 0x7f64a30ca000
mmap(0x7f64a30d3000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xef000) = 0x7f64a30d3000
mmap(0x7f64a30dc000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xf8000) = 0x7f64a30dc000
mmap(0x7f64a30e5000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x101000) = 0x7f64a30e5000
mmap(0x7f64a30ee000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x10a000) = 0x7f64a30ee000
mmap(0x7f64a30f7000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x113000) = 0x7f64a30f7000
mmap(0x7f64a3100000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x11c000) = 0x7f64a3100000
mmap(0x7f64a3109000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x125000) = 0x7f64a3109000
mmap(0x7f64a3112000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x12e000) = 0x7f64a3112000
mmap(0x7f64a311b000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x137000) = 0x7f64a311b000
mmap(0x7f64a3124000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x140000) = 0x7f64a3124000
mmap(0x7f64a312d000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x149000) = 0x7f64a312d000
mmap(0x7f64a3136000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x152000) = 0x7f64a3136000
mmap(0x7f64a313f000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x15b000) = 0x7f64a313f000
mmap(0x7f64a3148000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x164000) = 0x7f64a3148000
mmap(0x7f64a3151000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x16d000) = 0x7f64a3151000
mmap(0x7f64a315a000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x176000) = 0x7f64a315a000
mmap(0x7f64a3163000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x17f000) = 0x7f64a3163000
mmap(0x7f64a316c000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x188000) = 0x7f64a316c000
mmap(0x7f64a3175000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x191000) = 0x7f64a3175000
mmap(0x7f64a317e000, 36864, PROT_READ|PROT_WRITE,


```
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x19a000) = 0x7f64a317e000
mmap(0x7f64a3187000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1a3000) = 0x7f64a3187000
mmap(0x7f64a3190000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1ac000) = 0x7f64a3190000
mmap(0x7f64a3199000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1b5000) = 0x7f64a3199000
mmap(0x7f64a31a2000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1be000) = 0x7f64a31a2000
mmap(0x7f64a31ab000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1c7000) = 0x7f64a31ab000
mmap(0x7f64a31b4000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1d0000) = 0x7f64a31b4000
mmap(0x7f64a31bd000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1d9000) = 0x7f64a31bd000
mmap(0x7f64a31c6000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1e2000) = 0x7f64a31c6000
mmap(0x7f64a31cf000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1eb000) = 0x7f64a31cf000
mmap(0x7f64a31d8000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1f4000) = 0x7f64a31d8000
mmap(0x7f64a31e1000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1fd000) = 0x7f64a31e1000
mmap(0x7f64a31ea000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x206000) = 0x7f64a31ea000
mmap(0x7f64a31f3000, 36864, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x20f000) = 0x7f64a31f3000
close(4)
= 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libX11-xcb.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libX11-xcb.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libX11-xcb.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libX11-xcb.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libX11-xcb.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libX11-xcb.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
```

```
openat(AT_FDCWD, "tls/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "x86_64/libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "libX11-xcb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "/etc/ld.so.cache", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=41866, ...}) = 0
mmap(NULL, 41866, PROT_READ, MAP_PRIVATE, 4, 0) = 0x7f64b4c35000
close(4) = 0
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libX11-xcb.so.1",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\340\4\0\0\0\0\0"...
, 832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=5776, ...}) = 0
mmap(NULL, 2101288, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a2c00000
mprotect(0x7f64a2c01000, 2093056, PROT_NONE) = 0
mmap(0x7f64a2e00000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0) = 0x7f64a2e00000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-icccm.so.4",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxcb-icccm.so.4",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-icccm.so.4",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxcb-icccm.so.4",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxcb-icccm.so.4",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-icccm.so.4",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
```

```
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-icccm.so.4",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "libxcb-icccm.so.4", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-icccm.so.4",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0p\36\0\0\0\0\0"...,
832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=18368, ...}) = 0
mmap(NULL, 2113672, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a29f0000
mprotect(0x7f64a29f0000, 2093056, PROT_NONE) = 0
mmap(0x7f64a2bf3000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x3000) = 0x7f64a2bf3000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-image.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxcb-image.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-image.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxcb-image.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxcb-image.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-image.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
```

```
openat(AT_FDCWD, "tls/haswell/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-image.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-image.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "libxcb-image.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-image.so.0",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\200\20\0\0\0\0\0"...
, 832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=18536, ...}) = 0
mmap(NULL, 2113768, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a27e0000
mprotect(0x7f64a27e0000, 2093056, PROT_NONE) = 0
mmap(0x7f64a29e3000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x3000) = 0x7f64a29e3000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-shm.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxcb-shm.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-shm.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxcb-shm.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxcb-shm.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-shm.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
```

```
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "libxcb-shm.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-shm.so.0",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0P\r\0\0\0\0\0\0"..., 832)
= 832
fstat(4, {st_mode=S_IFREG|0644, st_size=10312, ...}) = 0
mmap(NULL, 2105448, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a25d0000
mprotect(0x7f64a25d2000, 2093056, PROT_NONE) = 0
mmap(0x7f64a27d1000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1000) = 0x7f64a27d1000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-keysyms.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxcb-keysyms.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-keysyms.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxcb-keysyms.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxcb-keysyms.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-keysyms.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
```

```
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-keysyms.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "libxcb-keysyms.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-keysyms.so.1",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0P\v\0\0\0\0\0"..., 832)
= 832
fstat(4, {st_mode=S_IFREG|0644, st_size=10232, ...}) = 0
mmap(NULL, 2105464, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a23c0000
mprotect(0x7f64a23c2000, 2093056, PROT_NONE) = 0
mmap(0x7f64a25c1000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1000) = 0x7f64a25c1000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-randr.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxcb-randr.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-randr.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxcb-randr.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxcb-randr.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
```

```
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-randr.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-randr.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "libxcb-randr.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-randr.so.0",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\0\0\0\3\0\>\0\1\0\0\0\340f\0\0\0\0\0"...
, 832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=63560, ...}) = 0
mmap(NULL, 2158696, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a21b0000
mprotect(0x7f64a21be000, 2097152, PROT_NONE) = 0
mmap(0x7f64a23be000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xe000) = 0x7f64a23be000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-render-util.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxcb-render-util.so.0"
, O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-render-util.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./lib/libxcb-render-util.so.0",
```

```
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/./bin/libxcb-render-util.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-render-util.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-render-util.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-render-util.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxcb-render-util.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-render-util.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-render-util.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-render-util.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/libxcb-render-util.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-render-util.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-render-util.so.0", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-render-util.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-render-util.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-render-util.so.0", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-render-util.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-render-util.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "libxcb-render-util.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-render-util.so.0",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\32\0\25\0\0\0\0\0"...
, 832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=14536, ...}) = 0
mmap(NULL, 2109848, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a1fa0000
mprotect(0x7f64a1fa3000, 2093056, PROT_NONE) = 0
mmap(0x7f64a21a2000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2000) = 0x7f64a21a2000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-render.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/././libxcb-render.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
```



```
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-render.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxcb-render.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxcb-render.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-render.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-render.so.0", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-render.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxcb-render.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-render.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-render.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-render.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/libxcb-render.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-render.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-render.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-render.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-render.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-render.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-render.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-render.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "libxcb-render.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-render.so.0",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\260L\0\0\0\0\0"...
, 832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=51288, ...}) = 0
mmap(NULL, 2146424, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a1d90000
mprotect(0x7f64a1d9c000, 2093056, PROT_NONE) = 0
mmap(0x7f64a1f9b000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xb000) = 0x7f64a1f9b000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-shape.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
```

```
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxcb-shape.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-shape.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxcb-shape.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxcb-shape.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-shape.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-shape.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "libxcb-shape.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-shape.so.0",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0@\20\0\0\0\0\0"...,
832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=14392, ...}) = 0
mmap(NULL, 2109528, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a1b80000
mprotect(0x7f64a1b83000, 2093056, PROT_NONE) = 0
mmap(0x7f64a1d82000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2000) = 0x7f64a1d82000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-sync.so.1",
```

```
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxcb-sync.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-sync.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxcb-sync.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxcb-sync.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-sync.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "libxcb-sync.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-sync.so.1",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\340 \0\0\0\0\0"... ,
832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=26712, ...}) = 0
mmap(NULL, 2121848, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a1970000
mprotect(0x7f64a1975000, 2097152, PROT_NONE) = 0
mmap(0x7f64a1b75000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x5000) = 0x7f64a1b75000
close(4) = 0
```

```
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-xfixes.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxcb-xfixes.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-xfixes.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxcb-xfixes.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxcb-xfixes.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-xfixes.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-xfixes.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "libxcb-xfixes.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-xfixes.so.0",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\200+\0\0\0\0\0"...
, 832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=30776, ...}) = 0
mmap(NULL, 2125912, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a1760000
mprotect(0x7f64a1767000, 2093056, PROT_NONE) = 0
mmap(0x7f64a1966000, 8192, PROT_READ|PROT_WRITE,
```

```
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x6000) = 0x7f64a1966000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-xinerama.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxcb-xinerama.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-xinerama.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxcb-xinerama.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxcb-xinerama.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-xinerama.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-xinerama.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-xinerama.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "libxcb-xinerama.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-xinerama.so.0",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\240\r\0\0\0\0\0",
832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=10296, ...}) = 0
mmap(NULL, 2105432, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a1550000
```

```
mprotect(0x7f64a1552000, 2093056, PROT_NONE) = 0
mmap(0x7f64a1751000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1000) = 0x7f64a1751000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-xkb.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxcb-xkb.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-xkb.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/../lib/libxcb-xkb.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/../bin/libxcb-xkb.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-xkb.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "libxcb-xkb.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-xkb.so.1",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0p\224\0\0\0\0\0"...
, 832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=112728, ...}) = 0
```

```
mmap(NULL, 2207864, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a1330000
mprotect(0x7f64a134a000, 2097152, PROT_NONE) = 0
mmap(0x7f64a154a000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1a000) = 0x7f64a154a000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libXext.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libXext.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libXext.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libXext.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libXext.so.6",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libXext.so.6", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "tls/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libXext.so.6", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "x86_64/libXext.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
openat(AT_FDCWD, "libXext.so.6", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file
or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libXext.so.6", O_RDONLY|O_CLOEXEC) =
4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\2205\0\0\0\0\0"...,
```

```
832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=73640, ...}) = 0
mmap(NULL, 2169496, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a1110000
mprotect(0x7f64a1121000, 2093056, PROT_NONE) = 0
mmap(0x7f64a1320000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x10000) = 0x7f64a1320000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxkbcommon-x11.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxkbcommon-x11.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxkbcommon-x11.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxkbcommon-x11.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxkbcommon-x11.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxkbcommon-x11.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxkbcommon-x11.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxkbcommon-x11.so.0", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxkbcommon-x11.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxkbcommon-x11.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxkbcommon-x11.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxkbcommon-x11.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/libxkbcommon-x11.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxkbcommon-x11.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxkbcommon-x11.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxkbcommon-x11.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxkbcommon-x11.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxkbcommon-x11.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxkbcommon-x11.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "x86_64/libxkbcommon-x11.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "libxkbcommon-x11.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxkbcommon-x11.so.0",
```



```
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0 (\0\0\0\0\0"... , 832)
= 832
fstat(4, {st_mode=S_IFREG|0644, st_size=31528, ...}) = 0
mmap(NULL, 2126584, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a0f00000
mprotect(0x7f64a0f07000, 2093056, PROT_NONE) = 0
mmap(0x7f64a1106000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x6000) = 0x7f64a1106000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxkbcommon.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxkbcommon.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxkbcommon.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxkbcommon.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxkbcommon.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxkbcommon.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxkbcommon.so.0",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "x86_64/libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "libxkbcommon.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
```

```
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxkbcommon.so.0",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\20@\0\0\0\0\0"...
, 832) = 832
fstat(4, {st_mode=S_IFREG|0644, st_size=256424, ...}) = 0
mmap(NULL, 2351480, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a0cc0000
mprotect(0x7f64a0cfd000, 2093056, PROT_NONE) = 0
mmap(0x7f64a0efc000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x3c000) = 0x7f64a0efc000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/avx512_1/x
86_64/libexpat.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/avx51
2_1/x86_64", 0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/avx512_1/l
ibexpat.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/avx51
2_1", 0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/x86_64/lib
expat.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/x86_6
4", 0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/libexpat.s
o.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell",
0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/avx512_1/x86_64/li
bexpat.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/avx512_1/x86_
64", 0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/avx512_1/libexpat.
so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/avx512_1",
0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/x86_64/libexpat.so
.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/x86_64",
0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/libexpat.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls",
0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
```

```
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/avx512_1/x86_64/libexpat.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/avx512_1/x86_64", 0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/avx512_1/libexpat.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/avx512_1", 0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/x86_64/libexpat.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/x86_64", 0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/libexpat.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell", 0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../avx512_1/x86_64/libexpat.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../avx512_1/x86_64", 0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../avx512_1/libexpat.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../avx512_1", 0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../x86_64/libexpat.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../x86_64", 0x7fffc17b0500) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../libexpat.so.1", O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\340=\0\0\0\0\0"..., 832) = 832
lseek(4, 64, SEEK_SET) = 64
read(4, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"..., 840) = 840
lseek(4, 179480, SEEK_SET) = 179480
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0K\336\216\20\227o\355\362\377\363\35P<-Qk"..., 36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=207888, ...}) = 0
lseek(4, 64, SEEK_SET) = 64
read(4, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"..., 840) = 840
mmap(NULL, 2300944, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) = 0x7f64a0a80000
mprotect(0x7f64a0aa7000, 2138112, PROT_NONE) = 0
mmap(0x7f64a0ca7000, 12288, PROT_READ|PROT_WRITE,
```

```
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x27000) = 0x7f64a0ca7000
mmap(0x7f64a0caa000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2b000) = 0x7f64a0caa000
mmap(0x7f64a0cab000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2c000) = 0x7f64a0cab000
mmap(0x7f64a0cac000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2d000) = 0x7f64a0cac000
mmap(0x7f64a0cad000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2e000) = 0x7f64a0cad000
mmap(0x7f64a0cae000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2f000) = 0x7f64a0cae000
mmap(0x7f64a0caf000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x30000) = 0x7f64a0caf000
mmap(0x7f64a0cb0000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x31000) = 0x7f64a0cb0000
mmap(0x7f64a0cb1000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x32000) = 0x7f64a0cb1000
close(4)
= 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../.././libuuid.so.1",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\340\24\0\0\0\0\0"... ,
832) = 832
lseek(4, 64, SEEK_SET)
= 64
read(4, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"... ,
952) = 952
lseek(4, 21984, SEEK_SET)
= 21984
read(4, "\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\373G\310\264+\272\214\4]'0\377l']n"... ,
36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=55088, ...}) = 0
lseek(4, 64, SEEK_SET)
= 64
read(4, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"... ,
952) = 952
mmap(NULL, 2152240, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a0870000
mprotect(0x7f64a0874000, 2134016, PROT_NONE) = 0
mmap(0x7f64a0a73000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x3000) = 0x7f64a0a73000
mmap(0x7f64a0a75000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x5000) = 0x7f64a0a75000
mmap(0x7f64a0a76000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x6000) = 0x7f64a0a76000
mmap(0x7f64a0a77000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x7000) = 0x7f64a0a77000
mmap(0x7f64a0a78000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x8000) = 0x7f64a0a78000
mmap(0x7f64a0a79000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x9000) = 0x7f64a0a79000
mmap(0x7f64a0a7a000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xa000) = 0x7f64a0a7a000
mmap(0x7f64a0a7b000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xb000) = 0x7f64a0a7b000
mmap(0x7f64a0a7c000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xc000) = 0x7f64a0a7c000
```

```
mmap(0x7f64a0a7d000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xd000) = 0x7f64a0a7d000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../.././libbz2.so.1",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0`\27\0\0\0\0\0"...,
832) = 832
lseek(4, 71448, SEEK_SET) = 71448
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\f\205\3008o\f\364\36\243\231i\317\177X\245X"...,
36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=87704, ...}) = 0
mmap(NULL, 2180760, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a0650000
mprotect(0x7f64a065f000, 2117632, PROT_NONE) = 0
mmap(0x7f64a085e000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xe000) = 0x7f64a085e000
mmap(0x7f64a0860000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x11000) = 0x7f64a0860000
mmap(0x7f64a0861000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x12000) = 0x7f64a0861000
mmap(0x7f64a0862000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x13000) = 0x7f64a0862000
mmap(0x7f64a0863000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x14000) = 0x7f64a0863000
mmap(0x7f64a0864000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x15000) = 0x7f64a0864000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../.././libpng15.so.15",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\00000\0\0\0\0\0"...,
832) = 832
lseek(4, 187880, SEEK_SET) = 187880
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\235\316z|\255\301<]J\233\321\0IC\360\363"...,
36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=218880, ...}) = 0
mmap(NULL, 2311936, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a0410000
mprotect(0x7f64a0439000, 2138112, PROT_NONE) = 0
mmap(0x7f64a0639000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x29000) = 0x7f64a0639000
mmap(0x7f64a063b000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2c000) = 0x7f64a063b000
mmap(0x7f64a063d000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2e000) = 0x7f64a063d000
mmap(0x7f64a063f000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x30000) = 0x7f64a063f000
mmap(0x7f64a0641000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x32000) = 0x7f64a0641000
mmap(0x7f64a0643000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x34000) = 0x7f64a0643000
```

```
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libdbus-1.so.3",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\200\343\0\0\0\0\0"...,
832) = 832
lseek(4, 64, SEEK_SET) = 64
read(4, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
840) = 840
lseek(4, 356160, SEEK_SET) = 356160
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\372\311\7\261\342\207\20\223` \16\244\362\3600~w"
..., 36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=470656, ...}) = 0
lseek(4, 64, SEEK_SET) = 64
read(4, "\1\0\0\0\5\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"...,
840) = 840
mmap(NULL, 2559616, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f64a0190000
mprotect(0x7f64a01de000, 2224128, PROT_NONE) = 0
mmap(0x7f64a03dd000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x4d000) = 0x7f64a03dd000
mmap(0x7f64a03df000, 312, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f64a03df000
mmap(0x7f64a03e0000, 20480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x52000) = 0x7f64a03e0000
mmap(0x7f64a03e5000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x57000) = 0x7f64a03e5000
mmap(0x7f64a03e9000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x5b000) = 0x7f64a03e9000
mmap(0x7f64a03ed000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x5f000) = 0x7f64a03ed000
mmap(0x7f64a03f1000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x63000) = 0x7f64a03f1000
mmap(0x7f64a03f5000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x67000) = 0x7f64a03f5000
mmap(0x7f64a03f9000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x6b000) = 0x7f64a03f9000
mmap(0x7f64a03fd000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x6f000) = 0x7f64a03fd000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/./libxcb-util.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../libxcb-util.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./libxcb-util.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./lib/libxcb-util.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/opt/Coreform-Cubit-2021.5/bin/./bin/libxcb-util.so.1",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/x86_64/libxcb-util.so.1",
```

```
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/avx512_1/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/x86_64/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/haswell/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/x86_64/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) =
-1 ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/avx512_1/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "tls/x86_64/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "tls/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/x86_64/libxcb-util.so.1", O_RDONLY|O_CLOEXEC)
= -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/avx512_1/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/x86_64/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "haswell/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "avx512_1/x86_64/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) = -1
ENOENT (No such file or directory)
openat(AT_FDCWD, "avx512_1/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT
(No such file or directory)
openat(AT_FDCWD, "x86_64/libxcb-util.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No
such file or directory)
openat(AT_FDCWD, "libxcb-util.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such
file or directory)
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libxcb-util.so.1",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0`%\0\0\0\0\0"..., 832)
= 832
fstat(4, {st_mode=S_IFREG|0644, st_size=22744, ...}) = 0
mmap(NULL, 2117896, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f649ff80000
mprotect(0x7f649ff85000, 2093056, PROT_NONE) = 0
mmap(0x7f64a0184000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x4000) = 0x7f64a0184000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../.././tls/haswell/avx512_1
/x86_64/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../.././tls/haswell/avx
512_1/x86_64", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../.././tls/haswell/avx512_1
/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../.././tls/haswell/avx
512_1", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
```

```
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/x86_64/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/x86_64", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/avx512_1/x86_64/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/avx512_1/x86_64", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/avx512_1/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/avx512_1", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/x86_64/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/x86_64", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/avx512_1/x86_64/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/avx512_1/x86_64", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/avx512_1/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/avx512_1", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/x86_64/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/x86_64", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../avx512_1/x86_64/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
```



```
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../avx512_1/x86_64", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../avx512_1/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../avx512_1", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../x86_64/libsystemd.so.0", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../x86_64", 0x7fffc17affa0) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../libsystemd.so.0", O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0@0\0\0\0\0\0"..., 832) = 832
lseek(4, 211088, SEEK_SET) = 211088
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\242\273\333E\216J\10Sa\252\213\37\276\317\250\2"
..., 36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=243032, ...}) = 0
mmap(NULL, 2336088, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) = 0x7f649fd40000
mprotect(0x7f649fd6f000, 2138112, PROT_NONE) = 0
mmap(0x7f649ff6f000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2f000) = 0x7f649ff6f000
mmap(0x7f649ff71000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x32000) = 0x7f649ff71000
mmap(0x7f649ff73000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x34000) = 0x7f649ff73000
mmap(0x7f649ff75000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x36000) = 0x7f649ff75000
mmap(0x7f649ff77000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x38000) = 0x7f649ff77000
mmap(0x7f649ff79000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x3a000) = 0x7f649ff79000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/avx512_1/x86_64/libcap.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/avx512_1/x86_64", 0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/avx512_1/libcap.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/avx512_1", 0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/x86_64/libcap.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/x86_64", 0x7fffc17aff40) = -1 ENOENT (No such file or directory)
```

```
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell/libcap
.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/haswell",
0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/avx512_1/x86_6
4/libcap.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/avx512_1/
x86_64", 0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/avx512_1/libca
p.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/avx512_1"
, 0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/x86_64/libcap.
so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/x86_64",
0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls/libcap.so.2",
O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../tls",
0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/avx512_1/x
86_64/libcap.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/avx51
2_1/x86_64", 0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/avx512_1/l
ibcap.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/avx51
2_1", 0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/x86_64/lib
cap.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/x86_6
4", 0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell/libcap.so.
2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../haswell",
0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../avx512_1/x86_64/li
bcap.so.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../avx512_1/x86_
64", 0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../avx512_1/libcap.so
.2", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../avx512_1",
```

```
0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../x86_64/libcap.so.2
", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../x86_64",
0x7fffc17aff40) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../libcap.so.2",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\20\26\0\0\0\0\0"...
, 832) = 832
lseek(4, 22048, SEEK_SET) = 22048
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0;\305e\340V\3\261\2757\256\0p\367\330\342"...
, 36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=39928, ...}) = 0
mmap(NULL, 2137080, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f649fb30000
mprotect(0x7f649fb34000, 2117632, PROT_NONE) = 0
mmap(0x7f649fd33000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x3000) = 0x7f649fd33000
mmap(0x7f649fd35000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x5000) = 0x7f649fd35000
mmap(0x7f649fd36000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x6000) = 0x7f649fd36000
mmap(0x7f649fd37000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x7000) = 0x7f649fd37000
mmap(0x7f649fd38000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x8000) = 0x7f649fd38000
mmap(0x7f649fd39000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x9000) = 0x7f649fd39000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../liblzma.so.5",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\2000\0\0\0\0\0"...
, 832) = 832
lseek(4, 163968, SEEK_SET) = 163968
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0;\227\301\223{s\246\234A*\226\320\201\fc"...
, 36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=183744, ...}) = 0
mmap(NULL, 2276800, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f649f900000
mprotect(0x7f649f925000, 2121728, PROT_NONE) = 0
mmap(0x7f649fb24000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x24000) = 0x7f649fb24000
mmap(0x7f649fb26000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x27000) = 0x7f649fb26000
mmap(0x7f649fb28000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x29000) = 0x7f649fb28000
mmap(0x7f649fb29000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2a000) = 0x7f649fb29000
mmap(0x7f649fb2a000, 4096, PROT_READ|PROT_WRITE,
```

```
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2b000) = 0x7f649fb2a000
mmap(0x7f649fb2b000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2c000) = 0x7f649fb2b000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././liblz4.so.1",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\360!\0\0\0\0\0"...,
832) = 832
lseek(4, 69024, SEEK_SET) = 69024
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\2\275v\343f\237\334\275\227#\312\251x\355\246S".
.., 36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=84920, ...}) = 0
mmap(NULL, 2177976, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f649f6e0000
mprotect(0x7f649f6ee000, 2117632, PROT_NONE) = 0
mmap(0x7f649f8ed000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0xd000) = 0x7f649f8ed000
mmap(0x7f649f8ef000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x10000) = 0x7f649f8ef000
mmap(0x7f649f8f0000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x11000) = 0x7f649f8f0000
mmap(0x7f649f8f1000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x12000) = 0x7f649f8f1000
mmap(0x7f649f8f2000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x13000) = 0x7f649f8f2000
mmap(0x7f649f8f3000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x14000) = 0x7f649f8f3000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././libgcrypt.so.11",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\205\0\0\0\0\0"...,
832) = 832
lseek(4, 571848, SEEK_SET) = 571848
read(4, "\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\321\353\374\217\342d\326
\360\230\356Tw-G5"..., 36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=603264, ...}) = 0
mmap(NULL, 2692224, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f649f440000
mprotect(0x7f649f4c3000, 2150400, PROT_NONE) = 0
mmap(0x7f649f6c3000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x83000) = 0x7f649f6c3000
mmap(0x7f649f6c7000, 400, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f649f6c7000
mmap(0x7f649f6c8000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x8a000) = 0x7f649f6c8000
mmap(0x7f649f6ca000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x8c000) = 0x7f649f6ca000
mmap(0x7f649f6cc000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x8e000) = 0x7f649f6cc000
mmap(0x7f649f6ce000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x90000) = 0x7f649f6ce000
```

```
mmap(0x7f649f6d0000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x92000) = 0x7f649f6d0000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././libgpg-error.so.0"
, O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\20F\0\0\0\0\0"...,
832) = 832
lseek(4, 152856, SEEK_SET) = 152856
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0W\245-\255(]\7\374\261\274m\301\230\225\34x"...,
36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=184552, ...}) = 0
mmap(NULL, 2277608, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f649f210000
mprotect(0x7f649f232000, 2134016, PROT_NONE) = 0
mmap(0x7f649f431000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x21000) = 0x7f649f431000
mmap(0x7f649f433000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x24000) = 0x7f649f433000
mmap(0x7f649f435000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x26000) = 0x7f649f435000
mmap(0x7f649f437000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x28000) = 0x7f649f437000
mmap(0x7f649f439000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2a000) = 0x7f649f439000
mmap(0x7f649f43b000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x2c000) = 0x7f649f43b000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././libdw.so.1",
O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\237\0\0\0\0\0"...,
832) = 832
lseek(4, 348936, SEEK_SET) = 348936
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0Y\31\200\224\327{\232T\321\274\352\206WC\266\t"..
., 36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=383960, ...}) = 0
mmap(NULL, 2472920, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f649efb0000
mprotect(0x7f649effe000, 2146304, PROT_NONE) = 0
mmap(0x7f649f1fe000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x4e000) = 0x7f649f1fe000
mmap(0x7f649f201000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x53000) = 0x7f649f201000
mmap(0x7f649f204000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x56000) = 0x7f649f204000
mmap(0x7f649f206000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x58000) = 0x7f649f206000
mmap(0x7f649f208000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x5a000) = 0x7f649f208000
mmap(0x7f649f20a000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x5c000) = 0x7f649f20a000
```

```
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/haswell/avx5
12_1/x86_64/libattr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/haswell
/avx512_1/x86_64", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/haswell/avx5
12_1/libattr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/haswell
/avx512_1", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/haswell/x86_
64/libattr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/haswell
/x86_64", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/haswell/liba
ttr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/haswell
", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/avx512_1/x86
_64/libattr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/avx512_
1/x86_64", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/avx512_1/lib
attr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/avx512_
1", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/x86_64/libat
tr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/x86_64"
, 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls/libattr.so.1
", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././tls",
0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././haswell/avx512_1
/x86_64/libattr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or
directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././haswell/avx
512_1/x86_64", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././haswell/avx512_1
/libattr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../.././haswell/avx
512_1", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
```

```
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../../../haswell/x86_64/libattr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../../../haswell/x86_64", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../../../haswell/libattr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../../../haswell", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../../../avx512_1/x86_64/libattr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../../../avx512_1/x86_64", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../../../avx512_1/libattr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../../../avx512_1", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../../../x86_64/libattr.so.1", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
stat("/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../../../x86_64", 0x7fffc17afd90) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../../../libattr.so.1", O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\320\23\0\0\0\0\0"..., 832) = 832
lseek(4, 21944, SEEK_SET) = 21944
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0&\27\354\306s\200G\342\7\256:\335\231\v\326\243"..., 36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=39768, ...}) = 0
mmap(NULL, 2136920, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) = 0x7f649eda0000
mprotect(0x7f649eda0000, 2117632, PROT_NONE) = 0
mmap(0x7f649efa3000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x3000) = 0x7f649efa3000
mmap(0x7f649efa5000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x5000) = 0x7f649efa5000
mmap(0x7f649efa6000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x6000) = 0x7f649efa6000
mmap(0x7f649efa7000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x7000) = 0x7f649efa7000
mmap(0x7f649efa8000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x8000) = 0x7f649efa8000
mmap(0x7f649efa9000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x9000) = 0x7f649efa9000
close(4) = 0
openat(AT_FDCWD,
"/opt/Coreform-Cubit-2021.5/bin/plugins/platforms/../../../../../../libelf.so.1", O_RDONLY|O_CLOEXEC) = 4
read(4, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0@0\0\0\0\0\0"..., 832)
```

```
= 832
lseek(4, 106240, SEEK_SET) = 106240
read(4,
"\4\0\0\0\24\0\0\0\3\0\0\0GNU\0\354\33\353\26w\203\320\217\325\365,1\307\7\310\3
63"... , 36) = 36
fstat(4, {st_mode=S_IFREG|0755, st_size=121840, ...}) = 0
mmap(NULL, 2214896, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x7f649eb80000
mprotect(0x7f649eb97000, 2117632, PROT_NONE) = 0
mmap(0x7f649ed96000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x16000) = 0x7f649ed96000
mmap(0x7f649ed98000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x19000) = 0x7f649ed98000
mmap(0x7f649ed99000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1a000) = 0x7f649ed99000
mmap(0x7f649ed9a000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1b000) = 0x7f649ed9a000
mmap(0x7f649ed9b000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1c000) = 0x7f649ed9b000
mmap(0x7f649ed9c000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x1d000) = 0x7f649ed9c000
close(4) = 0
mprotect(0x7f649ed96000, 4096, PROT_READ) = 0
mprotect(0x7f649efa3000, 4096, PROT_READ) = 0
mprotect(0x7f64a085e000, 4096, PROT_READ) = 0
mprotect(0x7f649fb24000, 4096, PROT_READ) = 0
mprotect(0x7f649f1fe000, 8192, PROT_READ) = 0
mprotect(0x7f649f431000, 4096, PROT_READ) = 0
mprotect(0x7f649f6c3000, 4096, PROT_READ) = 0
mprotect(0x7f649f8ed000, 4096, PROT_READ) = 0
mprotect(0x7f649fd33000, 4096, PROT_READ) = 0
mprotect(0x7f649ff6f000, 4096, PROT_READ) = 0
mprotect(0x7f64a0184000, 4096, PROT_READ) = 0
mprotect(0x7f64a03dd000, 4096, PROT_READ) = 0
mprotect(0x7f64a0639000, 4096, PROT_READ) = 0
mprotect(0x7f64a0a73000, 4096, PROT_READ) = 0
mprotect(0x7f64a0ca7000, 8192, PROT_READ) = 0
mprotect(0x7f64a0efc000, 8192, PROT_READ) = 0
mprotect(0x7f64a154a000, 4096, PROT_READ) = 0
mprotect(0x7f64a1106000, 4096, PROT_READ) = 0
mprotect(0x7f64a1320000, 4096, PROT_READ) = 0
mprotect(0x7f64a1751000, 4096, PROT_READ) = 0
mprotect(0x7f64a1966000, 4096, PROT_READ) = 0
mprotect(0x7f64a1b75000, 4096, PROT_READ) = 0
mprotect(0x7f64a1d82000, 4096, PROT_READ) = 0
mprotect(0x7f64a1f9b000, 4096, PROT_READ) = 0
mprotect(0x7f64a21a2000, 4096, PROT_READ) = 0
mprotect(0x7f64a23be000, 4096, PROT_READ) = 0
mprotect(0x7f64a25c1000, 4096, PROT_READ) = 0
mprotect(0x7f64a27d1000, 4096, PROT_READ) = 0
mprotect(0x7f64a29e3000, 4096, PROT_READ) = 0
mprotect(0x7f64a2bf3000, 4096, PROT_READ) = 0
mprotect(0x7f64a2e00000, 4096, PROT_READ) = 0
mprotect(0x7f64a3098000, 8192, PROT_READ) = 0
```



```
mprotect(0x7f64a34b7000, 28672, PROT_READ) = 0
mprotect(0x7f64a374f000, 8192, PROT_READ) = 0
mprotect(0x7f64a3acd000, 24576, PROT_READ) = 0
mprotect(0x7f64a3d71000, 4096, PROT_READ) = 0
access("/etc/system-fips", F_OK) = -1 ENOENT (No such file or directory)
munmap(0x7f64b4c35000, 41866) = 0
brk(0xa3d000) = 0xa3d000
socket(AF_UNIX, SOCK_STREAM|SOCK_CLOEXEC, 0) = 4
connect(4, {sa_family=AF_UNIX, sun_path=@" /tmp/.X11-unix/X0"}, 20) = -1
ECONNREFUSED (Connection refused)
close(4) = 0
socket(AF_UNIX, SOCK_STREAM|SOCK_CLOEXEC, 0) = 4
getsockopt(4, SOL_SOCKET, SO_SNDBUF, [0], [4]) = 0
setsockopt(4, SOL_SOCKET, SO_SNDBUF, [65536], 4) = 0
connect(4, {sa_family=AF_UNIX, sun_path="/tmp/.X11-unix/X0"}, 110) = -1 ENOENT
(No such file or directory)
close(4) = 0
stat("/etc/resolv.conf", {st_mode=S_IFREG|0644, st_size=218, ...}) = 0
openat(AT_FDCWD, "/etc/hosts", O_RDONLY|O_CLOEXEC) = 4
fstat(4, {st_mode=S_IFREG|0644, st_size=427, ...}) = 0
read(4, "# This file was automatically ge"... , 4096) = 427
read(4, "", 4096) = 0
close(4) = 0
socket(AF_INET, SOCK_STREAM|SOCK_CLOEXEC, IPPROTO_TCP) = 4
setsockopt(4, SOL_TCP, TCP_NODELAY, [1], 4) = 0
setsockopt(4, SOL_SOCKET, SO_KEEPALIVE, [1], 4) = 0
connect(4, {sa_family=AF_INET, sin_port=htons(6000),
sin_addr=inet_addr("127.0.0.1")}, 16) = -1 ECONNREFUSED (Connection refused)
close(4) = 0
clock_gettime(CLOCK_MONOTONIC, {tv_sec=2222, tv_nsec=694400700}) = 0
write(2, "qt.qpa.plugin: Could not load th"... , 91) = 91
write(2, "This application failed to start"... , 305) = 305
rt_sigprocmask(SIG_UNBLOCK, [ABRT], NULL, 8) = 0
rt_sigprocmask(SIG_BLOCK, ~[RTMIN RT_1], [], 8) = 0
getpid() = 175
gettid() = 175
tgkill(175, 175, SIGABRT) = 0
rt_sigprocmask(SIG_SETMASK, [], NULL, 8) = 0
--- SIGABRT {si_signo=SIGABRT, si_code=SI_TKILL, si_pid=175, si_uid=1000} ---
+++ killed by SIGABRT (core dumped) +++
```